

Thermo-regulated soldering iron gun with manual solder wire feed.



Technical data:

Voltage supply: 230 V 50 and 60 Hz

Max power: 80W

Power regulation: PWM from 0 to 100% Max temperature: 550°C @ 100%

Cable: 3 x 0.75 H03 Schuko male connector

Weight: 320 gr. Consist of:

• WSF 80

6 gr. Lead-free wire SACX0307 1mm coil

WB 10 1mm and WB 15 1.5mm wire-guide pipe

Empty spare coil2mm EX key

SF25 2,5 sqmm

INSTRUCTIONS

Choose a tube guide wire 1 or 1.5 mm suitable for wire diameter (use lead-free or SnPb alloys give 1mm min, max 1.5 mm).

Insert the end of the wire, perfectly straight, into the rear hole of the gun holding down the lever until the soldering tip, (check the correct insertion through the window).

Adjust the pre-load on the external spring acting on the knob, it is recommended to exercise the minimum pressure to avoid the deformation of the wire.

If the wire blocks, holding down the lever and pull it out, after cutting the deformed part, proceed to a new post. Connect the tool to the mains (230V ~) the indicator begins to flash.

TIN THE TIP AS SOON AS THE MELTING TEMPERATURE IS REACHED

Pushing the trigger, the wire advances toward the tip, for a length adjustable from 1 to 6 mm. To adjust the amount of wire needed, act on the grain, in front of the trigger; for adjusting the orientation of the wire to the tip, act on the grain beneath the thread guide

Model	Longlife curve Tips	Tubetti guidafilo	Max Temperature
WSF 80 80W-230V~ SF25 T0051384899	SF10 (Ø1.0) <i>T0051384999</i> SF15 (1.6) <i>T0051385099</i> SF25 (2.5) <i>T0051385199</i> SF40 (4.0) <i>T0051385299</i>	TB/70/10 Ø 1.0 <i>T0051385399</i> TB/70/15 Ø 1.5 <i>T0051385499</i>	100% = 550°C

READ THE FOLLOWING IMPORTANT INFORMATION REGARDING THE SAFETY USE OF THE DEVICE

Before connecting the appliance make sure that the nameplate data corresponds with the mains.

This appliance must only be used for the purpose it was designed.

Do not touch the appliance with wet hands and / or feet are wet.

Do not pull the cord or the appliance itself to remove the plug from the socket.

Before performing any maintenance, disconnect the appliance from the mains and allow to cool.

Do not use non-standard extensions (IMQ-VDE-NF-ETC..)

This tool can be placed on a holder when not in use

WARRANTY

Weller warrants this product against defects in workmanship for one year from date of purchase documented, in case of absence of such documentation will be considered the date of manufacture.

The warranty excludes all parts subject to wear.

The warranty is void in case of tampering or improper use of the device.

Transport costs are paid by the customer.

DICHIARAZIONE DI CONFORMITA' CE DECLARATION CE OF CONFORMITY

WELLER

Dichiara sotto la sua esclusiva responsabilità che il prodotto: Hereby declares under his own responsibility that the product:

Tipo - Type: gun type soldering iron Marchio - Brand: WELLER

Modello - Model: WSF 80 80W 230Vac

é di fabbricazione Italiana CEE - *Is made in Italy CEE* é conforme alle seguenti norme: Complies with the following regulations:

- 2006/95/CE DIRETTIVA BASSA TENSIONE
 2006/95/CE LOW VOLTAGE DIRECTIVE
- 2004/108/CE DIRETTIVA COMPATIBILITA' ELETTROMAGNETICA (EMC) 2004/108/CE ELECTROMAGNETIC COMPATIBILITY DIRECTIVE (EMC)
- 2002/96/CE DIRETTIVA SUI RIFIUTI DI APPARECCHIATURE ELETTRICHE ED ELETTRONICHE (RAEE) 2002/96/CE WASTE ELECTRICAL AND ELECTRONICAL EQUIPMENT DIRECTIVE (WEEE)

base a quanto previsto dalla Direttiva:

ricly in accordance with the requirements of the Directive:

 2006/42/CE – DIRETTIVA COMUNITARIA SULLE MACCHINE 2006/42/CE - COUNCIL DIRECTIVE ON MACHINERY

Amministratore Director

Date: 01 May 2012

www.weller-tools.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for weller manufacturer:

Other Similar products are found below:

SAS3210TRB 0052918099 0058736839 5BSA 0051612499 005 32 566 99 0054465399 PTH6 HE35 SP40NKUS T0051387699

T0051388399 T0051388799 T0051516199 T0052920699 T0053421699 T0053427699 T0053434699 T0053638699 T0058732869 PPT2

PSI5 HEW60P LT4X CT6E7 D550 D650 WPA2 DS209 DS227 RT6 RTW3MS EPH101 T0051390699 T0051612199 T0051628899

T0052704299 T0052922299 T0053422699 T0053429699 T0053440699 T0053657199 T0054480299 T0056104699N TC208 WTA3

WSTA6 WDH60 WPT15 WLSK200