6003 Joker combination wrench - Open-end with return angle of just 15. When things get tight.









**EAN:** 4013288219046 **Size:** 130x50x25 mm

Part number:05020220001Weight:35 gArticle number:6003 Joker ImperialCountry of origin:CZ

Customs tariff 82041100

number:

- Especially suitable for tight spaces
- The special mouth geometry expands the placement possibilities of the tool
- The low return angle in the mouth "takes" the screw every 15°
- Slim ring side angled by 15°
- With Take it easy tool finder: colour coding by size

As the installation space becomes increasingly tight during screwdriving, tools are necessary that enable users to work successfully even in such situations. Narrow spaces require additional placement points of the tool. Can spanners be modified so that the placement possibilities of the tool increase? The combination of the 7.5° pivoted mouth and the double hexagon geometry doubles the placement points. A repeated 180° turn of the wrench around the longitudinal axis during screwdriving provides four placement possibilities, and bolts or screw heads can be engaged every 15°. The Joker 6003 with its smart mouth geometry significantly expands the range of uses in confined spaces. The Joker 6003 will automatically find the respective placement point after every turn. The slim yet robust ring side is angled by 15° to the tool axis. The high-quality surface treatment achieves a high and long-lasting corrosion protection. With tool finder Take it easy: colour coding by size.

6003 Joker combination wrench - Open-end with return angle of just 15. When things get tight.



### For very tight spaces



The Joker 6003 ring spanner with its special mouth geometry mouth side pivoted by 7.5° and the double hexagon profile doubles the placement possibilities when repeatedly turning the wrench 180° around the longitudinal axis. Bolts and screw heads can be "accessed" every 15°. The Joker 6003 will automatically find the respective placement point after every turn.

Joker 6003: For pivoting angles under 30°




Thanks to the mouth side pivoted by 7.5°, double hexagon geometry and an adjusted application method (placement – screwdriving – turning – replacement – screwdriving – turning, etc), even screwdriving challenges allowing a pivoting angle of less than 30° can be solved.

## **Double-hex geometry**



The double hexagon geometry on the mouth and ring sides secures the positive connection with the screw head or bolt and reduces the risk of slipping.

#### Joker 6003: Angled ring side



The ring side is angled at 15° to the tool axis to prevent injury.

# "Take it easy" tool finder



Take it easy tool finder system - with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets).

6003 Joker combination wrench - Open-end with return angle of just 15. When things get tight.



Further versions in this product family:

|             | inch   | mm  | mm   | mm  | mm   | mm   |
|-------------|--------|-----|------|-----|------|------|
| 05020220001 | 1/4"   | 105 | 16   | 4   | 10   | 6    |
| 05020211001 | 5/16"  | 115 | 19   | 4.5 | 12.5 | 7    |
| 05020212001 | 3/8    | 125 | 22   | 5   | 15   | 7    |
| 05020213001 | 7/16"  | 135 | 24.5 | 5   | 17   | 8    |
| 05020214001 | 1/2"   | 160 | 26   | 6   | 19   | 8.5  |
| 05020215001 | 9/16"  | 167 | 29   | 6   | 20   | 8.5  |
| 05020216001 | 5/8"   | 182 | 35   | 6.5 | 23   | 10   |
| 05020217001 | 11/16" | 210 | 40   | 7.5 | 26   | 11.5 |
| 05020218001 | 3/4"   | 230 | 42   | 7.5 | 27.5 | 11.5 |

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Spanners category:

Click to view products by Wera manufacturer:

Other Similar products are found below:

74005 74008 1406504-3 1406504-4 1406504-5 1406504-7 1725859-2 9965 999-16625-001 G70515-18 1055265-1 1055267-1 1-1406504-0 1055787-1 DCH.91.251.PA TG70-18 TG70 G62748-11 DPH.99.005.2K DCP.91.045.TN 1055512-1 1055276-1 R282303020 TA-0456 DCA.91.149.0TN TA-0436 TA-0398 TOL-222901 74\_Z-0-0-193 294GB-5069-17-N 74\_Z-0-0-2 523200-4 294GB-5070-25-A 74\_Z-0-0-79 294GB-5070-17-A 74\_Z-0-0-321 TOL-171801 PR23350 1490262-2 9968 AC24VS 80117 DCN.91.149.0TK BT-A-6010CAGE R282340000 BT-BS-609WT BT-A-6000B R282303000 BT-BS-610R BT-BS-610RT