L-Keys for Hexagon Socket Screws







EAN: 4013288139429 **Size:** 90x6x2 mm

Part number:05022040001Weight:1 gArticle number:950 PKLSCountry of origin:CZ

Customs tariff 82041100

number:

• L-keys for hexagonal socket screws

- Hex-Plus allows socket head screws to live longer
- Extra-short arm for use on difficult-to-access screws
- · Hexagonal ballpoint on the long arm
- High corrosion protection thanks to chrome-plating

High quality L-keys with extra-short arm for applications on difficult-to-access screws. For hexagonal socket screws. The ball-end on the long arm allows for reliable working even in difficult installation situations. The precise chrome-plated design ensures high corrosion protection. The tools are quickly to hand thanks to the laser-engraved and thereby wear-resistant size markings on the L-keys.









L-Keys for Hexagon Socket Screws



L-Keys

With extra short arm

Hex-Plus

Ball tip



We questioned the classic L-key design, since all too often the screw head recess is rounded out, meaning screws can no longer be tightened or loosened - and so the user finds the L-key slipping out of the recess. Wera Hex-Plus tools have a larger contact surface in the screw head. The notching effects are reduced and thereby the deformation of the screws. At the same time, as much as 20 % more torque can be applied.



All users will recognise the need to saw or grind down L-keys to make them shorter for particularly confined screwdriving jobs. This has the disadvantage that they no longer have any corrosion protection at the separation point and secondly, they can become "soft" and therefore useless due to an alteration in the hardening during the shortening process.




Hexagon screws can endure a problem because the contact surfaces delivering the power from conventional tool, transferred to the screw via very small surface areas. The consequence: the screw can become damaged (rounding out). Hex-Plus tools have a greater contact surface that prevents this from happening! At the same time, as much as 20 % more torque can be applied. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, "around-the-corner" screwdriving jobs.

Size identification



The size of each L-keys has been engraved by a laser. In addition Take it easy L-keys have a colour coding according to sizes - for simple and rapid accessing of the required tool. Making it easy to find the right tool.

Surface protection



Chrome-plated hexagon L-keys for outstanding surface protection and long service life. High corrosion protection.

 $\label{linkhamma} Web \ link \\ https://products.wera.de/en/l-keys_l-keys_for_hexagon_socket_screws_950_pkls.html \\$

Wera - 950 PKLS 05022040001 - 4013288139429

L-Keys for Hexagon Socket Screws



Further versions in this product family:

	0	_ ^		L V	
	mm	mm	mm	inch	inch
050220400011)	1.5	90	4.5	3 1/2	11/64
05022041001	2.0	100	5.5	4	7/32
05022042001	2.5	112	6.5	4 7/16	1/4
05022043001	3.0	126	7.5	5	19/64
05022044001	4.0	140	10.0	5 1/2	25/64
05022045001	5.0	160	12	6 5/16	15/32
05022046001	6.0	180	15	7 1/16	19/32
05022047001	8.0	200	19	8	3/4
05022048001	10.0	219	22	8 5/8	7/8

¹⁾ Regular hexagon

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Tool Kits & Cases category:

Click to view products by Wera manufacturer:

Other Similar products are found below:

217434-1 4263 1055420-1 11-18-3023 63902-3270 63860-8170 856600-2 690372163 11-40-3247 63883-2870 63885-0270 63901-5670 63866-1070 63863-5070 63892-7370 11-18-3209 63860-4070 63881-0970 A0403641 11-18-3040 63865-2070 63910-1470 63861-5070 63850-7470 11-18-3201 63910-7570 FM 0501 146 63883-0670 63830-0070 63902-9170 11-18-3147 11-18-3079 63883-2670 63900-1770 11-18-3190 63851-1070 63912-4770 63911-5270 63895-1070 63860-1470 63850-6070 1-69411-3 63852-9270 63802-6270 63902-4870 11-18-3202 63852-9170 63850-1070 63830-0170 63910-2870