L-Keys for Hexagon Socket Screws









- L-keys for hexagonal socket screws
- · Hex-Plus allows socket head screws to live longer
- Rubber sleeve for pleasant grip
- Hexagonal ballpoint on the long arm
- BlackLaser for high corrosion protection and long service life

Wera L-keys with finger-protecting plastic sleeves for imperial socket head screws. This means they are ergonomic and pleasant to grip even in cold temperatures. The Hex Plus profile offers a greater contact surface in the head of the screw. The notching effect is therefore reduced to a minimum and damage to the screw head more or less eliminated. The ballpoint on the long arm allows dependable working even in difficult installation situations. The BlackLaser surface treatment provides outstanding surface protection, even against corrosion, and a long service life. Laser-engraved and thereby wear-resistant size markings on the L-keys for rapid accessing.

950 SPKL L-key Multicolour, Imperial, 5/16" x 195 mm

L-Keys for Hexagon Socket Screws



L-keys with a thermoplastic sleeve

Hex-Plus

```
Ball tip
```



We questioned the classic L-key design, since all too often the screw head recess is rounded out, meaning screws can no longer be tightened or loosened - and so the user finds the L-key slipping out of the recess. Wera Hex-Plus tools have a larger contact surface in the screw head. The notching effects are reduced and thereby the deformation of the screws. At the same time, as much as 20 % more torque can be applied.



L-keys made from circular material fit into the hand better and allow less strenuous work over a longer period. Additionally, the rubber sleeve provides a pleasant grip, particularly in applications at low temperatures. Colour coding and large stamp enable the desired Lkey to be easily located. Moreover, the round material keys are more robust, particularly where smaller sizes are concerned.



Hexagon screws can endure a problem because the contact surfaces delivering the power from the conventional tool, is transferred to the screw via very small surface areas. The consequence: the screw can become damaged (rounding out). Hex-Plus tools have a greater contact surface that prevents this from happening! At the same time, as much as 20 % more torque can be applied. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!



The spherical drive profile means that it is possible to swivel the axis of the tool to that of the screw, and therefore enable angled, "around-the-corner" screwdriving jobs.

Take it easy tool finder system



Take it easy tool finder system with profile and size colour-coding for quick and easy tool selection. Colour-coded system for hexagon drive screws (L-Keys, Zyklop bit sockets), external hex drive screws and nuts (Joker wrenches, Zyklop sockets and Zyklop bit sockets with holding function), and TORX® drive screws (L-Keys, Zyklop bit sockets). L-Keys for Hexagon Socket Screws



Further versions in this product family:

	O inch	L ↓ mm	mm	inch	inch
05022630001	5/64	101	16	4	5/8
05022631001	3/32	112	19	4 7/16	3/4
05022632001	1/8	123	21	4 7/8	27/32
05022633001	5/32	137	24	5 3/8	1
05022634001	3/16	154	27	6 1/16	1 1/16
05022635001	7/32	172	31	6 3/4	1 1/4
05022636001	1/4	185	34	7 1/4	1 5/16
05022637001	5/16	195	37	7 11/16	1 7/16
05022638001	3/8	224	42	9	1 11/16

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Tool Kits & Cases category:

Click to view products by Wera manufacturer:

Other Similar products are found below :

217434-1 4263 1055420-1 11-18-3023 63902-3270 63860-8170 856600-2 690372163 11-40-3247 63883-2870 63885-0270 63901-5670 63866-1070 63863-5070 63892-7370 11-18-3209 63860-4070 63881-0970 A0403641 11-18-3040 63865-2070 63910-1470 63861-5070 63850-7470 11-18-3201 63910-7570 FM 0501 146 63883-0670 63830-0070 63902-9170 11-18-3147 11-18-3079 63883-2670 63900-1770 11-18-3190 63851-1070 63912-4770 63911-5270 63895-1070 63860-1470 63850-6070 1-69411-3 63852-9270 63802-6270 63902-4870 11-18-3202 63852-9170 63850-1070 63830-0170 63910-2870