## **Bits for Square Socket Screws**









EAN: 4013288041296 Size: 50x7x6 mm Part number: Weight: 05060149001 11 g Article number: 868/4 BTZ Square-Plus Country of origin: CZ

**Customs tariff** 

82079030

number:

- Suitable for square socket screws
- Ductile and tough for hard materials
- BiTorsion zone to absorb peak loads
- 1/2" square socket drive
- Take it easy tool finder: colour coding according to profile and size

BiTorsion bits for square socket screws with elastic Torsion zone - where kinetic energy is diverted from peak loads - and softer BiTorsion zone to prevent the bit tip from twisting under peak loads. This greatly extends the product service life. This provides the best possible durability together with the matching holder. Tough viscous for universal use. 1/4" hexagon, suitable for holders as per DIN ISO 1173-F 6.3.

#### **Bits for Square Socket Screws**



#### **BiTorsion Bits**

## Two cushioning torsion zones

## BiTorsion phase 1


### BiTorsion phase 2




Peak forces that occur in power tool applications often result in premature wear of bits or damage to the screw head. This usually occurs during initial power-up and the when the screw comes to a standstill. Screwdriving could become more productive and safer if these peak loads could be minimised. The Wera BiTorsion system prevents premature wear. The service life of the tool is extended and the productivity of applications power tool significantly increased.



The effectiveness of the BiTorsion system comes from a combination of two shock-absorbing spring elements. Both bits as well as holders have a cushioning torsion zone that diverts the kinetic energy away from the drive tip during peak loads.




The torsion spring integrated into the unique BiTorsion holder absorbs lower levels of peak loads (Phase 1). Any overloading of this spring is effectively prevented by means of a supporting mechanism.



Higher peak loads are minimised through the torsion effect of the bit shaft (Phase 2). This effect is achieved with a specific heat treatment after the hardening process of the bits. This reduces the hardness of the shaft in comparison to the drive tip.

## Above-average service life



Even the service life of conventional bits is enhanced with the use of the BiTorsion holder and the BiTorsion bit also functions in a normal holder.

#### Prevents premature wear



The optimally coordinated features of the torsion zones on the bit and holder permit a phased yield when under strain. The two-phase system prevents premature wear. Moreover, a long tool service life is also ensured by the hardness of the bits that matches the respective application.

# BiTorsion and conventional tools



The BiTorsion holder and the BiTorsion bit can, of course, be used independently of one another.

Web link

https://products.wera.de/en/bits\_holders\_adaptors\_the\_range\_of\_bits\_bits\_for\_square\_socket\_screws\_868\_4\_btz\_square-plus.html

Wera - 868/4 BTZ Square-Plus 05060149001 - 4013288041296

**Bits for Square Socket Screws** 



## Further versions in this product family:

	0	<b>\  \  \  \  \ </b>	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	$\varnothing$
		mm	inch	mm
05060147001	#1	50	2	4.2
05060148001	#2	50	2	4.2
05060149001	#3	50	2	5.5

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Screwdrivers, Nut Drivers & Socket Drivers category:

Click to view products by Wera manufacturer:

Other Similar products are found below:

272012M 27850 CE-16-03400-00-HNDLE-TORQ 323451-000 HMM-HH WUVT-1-120AC-P 00-8987-YWPP 32024 XW4Z-00B
49-22-4073 96025 96030 96560 96430 31830 92270 96012 96436 96536 92064 72820 96520 92040 96416 96570 72823 96525 96720
31832 92020 96523 96510 96427 92073 92052 72905 72741 72663 32061 30751 130203/TA KLEIN TOOLS SCREWDRIVER 4-IN-1
612020B 35-045 6951 83 9058 9977 EMF PTE6