Bits for TORX PLUS® Screws







EAN: 4013288031549 **Size:** 25x7x7 mm

Part number:05066280001Weight:5 gArticle number:867/1 IP TORX PLUS®Country of origin:CZ

Customs tariff 82079030

number:

• For TORX PLUS® screws

- Ductile and tough for hard materials
- 1/4" hexagon drive (Wera connecting series 1)
- Suitable for Bosch, Fein, Holz-Her, Lecreux, Metabo
- Prevents premature breakage of the drive tip

High quality bits for recessed TORX PLUS® screws. TORX PLUS® profile: in comparison to normal TORX® profiles, the enlargement of the 6 torque-transferring flanks between the tool and the screw is effected by means of an ellipse-shaped profile design and not a circular one. This means that the power applied when screwdriving is spread over a larger area. Higher torque is transferred and the service life of the screw and tool is also enhanced. Extra-hard. ¼" hexagon, suitable for holders as per DIN ISO 1173-D 6.3.

Web link

 $https://products.wera.de/en/bits_holders_adaptors_the_range_of_bits_bits_for_torx_plus_screws_867_1_ip_torx_plus.html$

Wera - 867/1 IP TORX PLUS® 05066280001 - 4013288031549

Bits for TORX PLUS® Screws



TORX PLUS®



Compared with the "normal" TORX® profile, the elliptical instead of circular profile enlarges the 6 flanks that transfer torque between the tool and the screw. This means that the force applied when screwdriving is spread across a larger surface area. Higher torque is transferred and, in addition, the service life of the screw and tool are lengthened. The so-called centre-lock screws on cutting tools represent a typical use of this type of screw profile. The thermal influences on such holders for carbide insert tips often "bake" the retaining screws so firmly that it is important to have a profile that considerably enhances the loosening torque capability of the screws. For this reason a torque-stable screw profile is necessary to avoid any possible damage to the screw and to exclude the possibility of an otherwise costly machine downtime.

Tough-absorbing bits



Tough-absorbing Wera bits (Z) prevent any premature breakage of the drive tip.

867/1 IP TORX PLUS® bits, 10 IP x 25 mm

Bits for TORX PLUS® Screws



Further versions in this product family:

	\odot	\[\frac{\lambda}{\psi} \]	A v
		mm	inch
05135120001	IP 1	25	1
05135121001	2 IP	25	1
05160956001	3 IP	25	1
05134695001	4 IP	25	1
05066272001	5 IP	25	1
05066274001	6 IP	25	1
05066276001	7 IP	25	1
05066278001	8 IP	25	1
05066279001	9 IP	25	1
05066280001	10 IP	25	1
05066282001	15 IP	25	1
05066284001	20 IP	25	1
05066286001	25 IP	25	1
05066287001	27 IP	25	1
05066288001	30 IP	25	1
05066290001	40 IP	25	1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Screwdrivers, Nut Drivers & Socket Drivers category:

Click to view products by Wera manufacturer:

Other Similar products are found below:

272012M 27850 CE-16-03400-00-HNDLE-TORQ 323451-000 HMM-HH WUVT-1-120AC-P 00-8987-YWPP 32024 XW4Z-00B
49-22-4073 96025 96030 96560 96430 31830 92270 96012 96436 96536 92064 72820 96520 92040 96416 96570 72823 96525 96720
31832 92020 96523 96510 96427 92073 92052 72905 72741 72663 32061 30751 130203/TA KLEIN TOOLS SCREWDRIVER 4-IN-1
612020B 35-045 6951 83 9058 9977 EMF PTE6