# Tool sets for concrete applications











Part number:05075681001Weight:3366 gArticle number:Click-Torque C 3 Set 2Country of origin:CZ

Customs tariff 82041200

number:

- For fitting security-relevant cement screws with defined torque moments as per screw manufacturer instructions
- Click-Torque C 3 torque wrench with reversible ratchet (measuring range: 40-200 Nm; precision ± 3 % as per DIN EN ISO 6789-1:2017-07)
- 8790 C Impaktor socket wrench inserts for the application with compressed air or electrically driven impact wrenches with 12.5 mm = 1/2" drive (13 mm to 21 mm)
- Extension 8894 SC, short, ½" with cross-bore and the ring socket to secure the locking ring/locking pin of machine operated tools
- 11-piece set in premium textile tool box

11-piece set for fitting security-relevant cement screws with defined torque moments as per screw manufacturer instructions. With Take it easy tool finder with colour coding and size stamping - for easy and fast location of the required tool.













# Tool sets for concrete applications



## Set contents:



# Click-Torque C 3

05075622001 1 x 1/2" x 40-200 Nm



# 8790 C Impaktor

05004570001	1 x 13 x 38 mm
05004571001	1 x 14 x 38 mm
05004572001	1 x 15 x 38 mm
05004573001	1 x 16 x 38 mm
05004574001	1 x 17 x 38 mm
05004575001	1 x 18 x 38 mm
05004576001	1 x 19 x 38 mm
05004577001	1 x 20 x 38 mm
05004578001	1 x 21 x 38 mm



## 8894 SC

1 x 1/2" x 125 mm

# For fitting cement screws



The tool set is particularly suitable for fitting security-relevant cement screws with defined torque moments as per screw manufacturer instructions

# For electric or pneumatic impact wrenches



The Impaktor technology ensures above-average service life of the Impaktor socket wrench plug-ins even under extreme conditions.

# Cross-bore and ring socket



Due to the groove and the ring socket, the tool can be secured with a locking pin or O-ring on the power tool.

# **Click-Torque Wrench series**



Click torque wrench in unmistakable Wera design.

## **Exact**

# ±3 % DIN EN ISO 6789-1:2017-07

Precise to  $\pm$  3% as per DIN EN ISO 6789-1:2017-07.

## Simple and safe




Easy setting and saving of the desired torque value; readable on the main and fine scales.

## Simple setting



With audible and tactile clicks when adjusting the scale values.

## Release mechanism



When the set torque value is reached, an audible and tactile mechanism triggers.

Web link

 $https://products.wera.de/en/tools\_by\_trade\_tool\_sets\_for\_concrete\_applications\_click-torque\_c\_3\_set\_2.html$ 

Wera - Click-Torque C 3 Set 2 05075681001 - 4013288217561

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Spanners category:

Click to view products by Wera manufacturer:

Other Similar products are found below:

74005 74008 1406504-3 1406504-4 1406504-5 1406504-7 1725859-2 9965 999-16625-001 G70515-18 1055265-1 1055267-1 1-1406504-0 1055787-1 DCH.91.251.PA TG70-18 TG70 G62748-11 DPH.99.005.2K DCP.91.045.TN 1055512-1 1055276-1 R282303020 TA-0456 DCA.91.149.0TN TA-0436 TA-0398 TOL-222901 74\_Z-0-0-193 294GB-5069-17-N 74\_Z-0-0-2 523200-4 294GB-5070-25-A 74\_Z-0-0-79 294GB-5070-17-A 74\_Z-0-0-321 TOL-171801 PR23350 1490262-2 9968 AC24VS 80117 DCN.91.149.0TK BT-A-6010CAGE R282340000 BT-BS-609WT BT-A-6000B R282303000 BT-BS-610R BT-BS-610RT