



<b>EAN:</b>	4013288195708	<b>Size:</b>	50x7x7 mm
<b>Part number:</b>	05134937001	<b>Weight:</b>	7 g
<b>Article number:</b>	851/4 ADC PH	<b>Country of origin:</b>	CZ
		<b>Customs tariff number:</b>	82079030

- For Phillips screws
- Particularly hard for semi-hard materials
- Diamond coating for a secure fit in the screw, literally bites into the screwhead to prevent cam-out
- Profiled version
- 1/4" hexagon drive (Wera connecting series 4)

High quality Wera bit for Phillips screws. Comes with a sharp-edged profile which breaks away the paint when e.g. screw profiles are covered in it and this ensures a dependable transfer of power between the bit and screw. The diamond coating ensures a secure fit of the bit in the screw, reduces the contact pressure required and lowers the risk of slipping. Extra-hard design. 1/4" hexagon, suitable for holders as per DIN ISO 1173-F 6.3.

**Web link**

[https://products.wera.de/en/bits\\_holders\\_adaptors\\_the\\_range\\_of\\_bits\\_bits\\_for\\_phillips\\_screws\\_851\\_4\\_adc\\_ph.html](https://products.wera.de/en/bits_holders_adaptors_the_range_of_bits_bits_for_phillips_screws_851_4_adc_ph.html)

Wera - 851/4 ADC PH  
05134937001 - 4013288195708

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)


## Bits for Phillips Screws

## A-Bits



A stands for aviation. A bits are particularly hard bits with a sharp-edged profile which e.g. penetrates screw profiles full of paint (such as on fuselage panels) ensuring a dependable transfer of force between the bit and the screw.

## Reduced cam-out forces




The minute diamond particles applied to the tip of the tool literally "bite" into the screw and ensure an exact, anti-slip fit in the head of the screw. This secure fit protects the screw. The cam-out forces which compel the user to apply greater pressure to the screw are considerably reduced.

## Secure fit in the screw head







Today, the Wera diamond bit - manufactured with the technology specifically developed by Wera for this application - still sets the standard in terms of resilience and functionality. Wera bits with a diamond coating ensure a secure fit of the bit in the screw head.

## Perfect fit



Ideal for sensitive materials

## Further versions in this product family:

		 mm	 inch	 mm
<b>05134937001</b>	<b>PH 0</b>	<b>50</b>	<b>2</b>	<b>3.0</b>
05134938001	PH 0	89	3 1/2	3.0
05134939001	PH 0	152	6	3.0
05134950001	PH 1	50	2	4.5
05134943001	PH 1	89	3 1/2	4.5
05134946001	PH 1	152	6	4.5
05134951001	PH 2	50	2	6.0
05134944001	PH 2	89	3 1/2	6.0
05134947001	PH 2	152	6	6.0
05134952001	PH 3	50	2	-
05134945001	PH 3	89	3 1/2	-
05134948001	PH 3	152	6	-

## Web link

[https://products.wera.de/en/bits\\_holders\\_adaptors\\_the\\_range\\_of\\_bits\\_bits\\_for\\_phillips\\_screws\\_851\\_4\\_adc\\_ph.html](https://products.wera.de/en/bits_holders_adaptors_the_range_of_bits_bits_for_phillips_screws_851_4_adc_ph.html)

Wera - 851/4 ADC PH  
05134937001 - 4013288195708

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: info@wera.de

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Screwdrivers, Nut Drivers & Socket Drivers](#) category:*

*Click to view products by [Wera](#) manufacturer:*

Other Similar products are found below :

[272012M](#) [27850](#) [CE-16-03400-00-HNDLE-TORQ](#) [323451-000](#) [HMM-HH](#) [WUVT-1-120AC-P](#) [00-8987-YWPP](#) [32024](#) [TL10416](#) [XW4Z-00B](#) [49-22-4073](#) [96025](#) [96030](#) [96560](#) [96430](#) [31830](#) [92270](#) [96012](#) [96436](#) [96536](#) [92064](#) [72820](#) [96520](#) [92040](#) [96416](#) [96570](#) [72823](#) [96525](#) [96720](#) [31832](#) [92020](#) [96523](#) [96510](#) [96427](#) [92073](#) [92052](#) [72905](#) [72741](#) [72663](#) [32061](#) [30751](#) [130203/TA](#) [KLEIN TOOLS SCREWDRIVER](#) [4-IN-1](#) [612020B](#) [35-045](#) [6951](#) [83](#) [9058](#) [9977](#) [EMF](#)