



894

LED Traffic Light

NEW



LED Traffic Light (2 tier)



LED Traffic Light (3 tier)



Clear lenses ensure signalling effect even in direct sunlight

- High visibility LED Traffic Light in an innovative design
- Clear signalling even in direct sunlight thanks to clear lenses
- Simple mounting thanks to integrated mounting bracket
- Very good sideward visibility

TECHNICAL SPECIFICATIONS:

Dimensions (D x W x H):	2 tier: 136 mm x 85 mm x 311 mm	
	3 tier: 136 mm x 85 mm x 396 mm	
Housing:	PC/ABS, grey	
Lens:	PC, transparent	
Fixing:	wall mounting	
Installation position:	vertical/hanging	
Connection:	Screwable connection with wire protection max. 1.5 mm ²	
Cable entry:	Cable diameter max. 13 mm	
Duty cycle:	100 % ED	

Life duration up to 50,000 hrs

ORDER SPECIFICATIONS:

Voltage	24 V =	115 to 230 V ~
Current Consumption	60 mA (red/yellow)	30 mA per tier at 230 V/50 Hz
	120 mA (green)	
red / green	894 160 55	894 160 68
red / yellow / green	894 180 55	894 180 68

ACCESSORIES:

Additional Fixing Bow underneath (see page 145)	975 894 01
---	-------------------


TECHNICAL DIAGRAMS:

see page 299



High visibility LED Traffic Light with integrated siren see page 180

In preparation





LED Beacon (1 tier)



Innovative design option with the attachment of a second fixing bow (accessory)



The direction of the optical signal can be individually adjusted

- High visibility LED Beacon / Traffic Light in an innovative design
- Colour intensive light effect thanks to LEDs in the same colour as the lenses
- Simple mounting thanks to integrated mounting bracket
- Very good sideward visibility

i TECHNICAL SPECIFICATIONS:	
Dimensions (D x W x H):	1 tier: 136 mm x 85 mm x 226 mm
	2 tier: 136 mm x 85 mm x 311 mm
	3 tier: 136 mm x 85 mm x 396 mm
Housing:	PC/ABS, grey
Lens:	PC, transparent
Fixing:	wall mounting
Installation position:	vertical/hanging
Connection:	Screwable connection with wire protection max. 1.5 mm ²
Cable entry:	Cable diameter max. 13 mm
Duty cycle:	100 % ED

Life duration up to 50,000 hrs

ORDER SPECIFICATIONS:		
Voltage	24 V =	115 to 230 V ~
Current Consumption	60 mA (red/yellow)	30 mA per tier at 230 V/50 Hz
	120 mA (green)	
red	894 010 55	894 010 68
green	894 020 55	894 020 68
yellow	894 030 55	894 030 68
red / green	894 060 55	894 060 68
red / yellow / green	894 080 55	894 080 68

ACCESSORIES:	
Additional Fixing Bow underneath	975 894 01

TECHNICAL DIAGRAMS:	
see page 299	



High visibility LED Traffic Light with integrated siren see page 181

In preparation



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [LED Lighting Fixtures](#) category:

Click to view products by [Werma](#) manufacturer:

Other Similar products are found below :

[XVEC21P](#) [XVEC2B7](#) [113163000-00662717](#) [113472000-00691461](#) [LD6A-3DQB-RYG](#) [LF1B-NA3P-2THWW2-3M](#) [LF1B-NC3P-2THWW2-3M](#) [LF1B-ND3P-2THWW2-3M](#) [E35600](#) [NB-RLAMP01-LED](#) [FLK7LED](#) [LD6A-3WQB-RYG](#) [XVC4B3K](#) [XVBC4M7](#) [2702482](#) [2702935](#) [ZWF-638-24CW](#) [ZAF-486-24CW](#) [BC5000-N-S](#) [BP3200-C-S-24](#) [BP3200-C-F-36](#) [BP3200-C-F-12](#) [BC5000-C-S](#) [2403122](#) [2403121](#) [2402991](#) [113261000-00641180](#) [113259000-00641174](#) [190007019-00014904](#) [226108019-00610754](#) [4823](#) [4824](#) [4866](#) [4868](#) [11212573001-00514271](#) [113021000-00564565](#) [113473000-00704968](#) [113471000-00704981](#) [NB-RLAMP01](#) [E35500](#) [408001403-00671626](#) [LD6A-3WZQB-RYG](#) [LF1B-NA4P-2THWW2-3M](#) [LF1B-NB3P-2THWW2-3M](#) [LF1D-C2F-2W-330](#) [LF1D-LH2F-2W-A](#) [LF1B-ND4P-2THWW2-3M](#) [LF1B-NF3P-2THWW2-3M](#) [SL7/4-FW](#) [BC5500-C-S-12](#)