





Black DC Power Cable 1.5m long
Plug 2.1x5.5 mm – straight
Socket 2.1x5.5 mm
 flexible, multiwire conductors,
 stranded of bare copper wires
 coaxial **0.50mm²**



| Model | P21-C21-C050-150BK |
|---------------------------------|---|
| DC Plug (output) | 2.1x5.5mm, straight (round plug, outer diameter 5.5mm, inner diameter 2.1mm) |
| DC Socket (input) | 2.1x5.5mm, straight (round socket, outer diameter 2.1mm, inner diameter 5.5mm) |
| Construction | flexible, multiwire conductors, stranded of bare annealed copper wires - coaxial |
| Cable cross section | 3.6mm |
| Wire diameter | 0.5mm² |
| Nominal voltage | 0-100V |
| Rated current | 2A |
| Length | 150cm |
| Jacket | PVC |
| Color | Black |
| Inner conductor | Cu |
| Insulation resistance | >100MΩ @ 500VDC |
| Insulation thickness | 0.4mm |
| Allowable operation temperature | -20°C to 70°C |
| Maximum wire resistance | 39.0 Ω/km @ 20°C |



| Marking System | | | | model: P21-C21-C050-150BK | | | | | | | |
|----------------|--|----------|----------|----------------------------------|---|----------|------------|----------|------------|-----------|--|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | | | | |
| P | 21 | - | C | 21 | - | C | 050 | - | 150 | BK | |
| 1 | Input / Output (side 1) | | | | P - straight plug A - angled plug C - socket | | | | | | |
| 2 | Plug / Socket dimensions (side 1) | | | | 07 - 0.7mm / 2.35mm 13 - 1.3mm / 3.5mm 40 - 1.7mm x 4.0mm 48 - 1.7mm x 4.8mm 55 - 1.7mm / 5.5mm 21 - 2.1mm / 5.5mm 25 - 2.5mm x 5.5mm | | | | | | |
| 3 | Input / Output (side 2) | | | | P - straight plug A - angled plug C - socket | | | | | | |
| 4 | Plug / Socket dimensions (side 2) | | | | T - tinned terminals 07 - 0.7mm / 2.35mm 13 - 1.3mm / 3.5mm 40 - 1.7mm x 4.0mm 48 - 1.7mm x 4.8mm 55 - 1.7mm / 5.5mm 21 - 2.1mm / 5.5mm 25 - 2.5mm x 5.5mm | | | | | | |
| 5 | cable type | | | | C- YTLYek (coaxial) T- TLYP | | | | | | |
| 6 | wire diameter | | | | 035 - 0.35mm ² 050 - 0.5mm ² 075 - 0.75mm ² 100 - 1.0mm ² | | | | | | |
| 7 | length | | | | 050 - 500mm 150 - 1500mm | | | | | | |
| 8 | color | | | | BK - black WH - white TR - transparent | | | | | | |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DC Power Cords](#) category:

Click to view products by [WEST POL](#) manufacturer:

Other Similar products are found below :

[2R6006A20A120](#) [172-4000](#) [172-4101](#) [21033836407](#) [2J-1865A](#) [2R7006A20A120](#) [426055400-3](#) [420680840-3](#) [96CB-POWER-B-1.8M2](#)
[2052KH2-BK](#) [804001P03M050G](#) [2050KH1-BK](#) [216603-0037](#) [862545-5](#) [BXC-10567](#) [172-2555](#) [32102-022800-200-RS](#) [DC.CAB.8000.0300](#)
[DC.CAB.6400.0200](#) [AK-ND-C07](#) [AK-ND-C16](#) [DC.CAB.4600.0200](#) [DC.CAB.8400.0020](#) [DC.CAB.4201.0150](#) [DC.CAB.8200.0300](#)
[DC.CAB.6601.0200](#) [DC.CAB.6601.0020](#) [DC.CAB.4201.0200](#) [DC.CAB.8010.0020](#) [AK-ND-C12](#) [AK-ND-C06](#) [DC.EXT.4200.0300](#)
[DC.EXT.6200.0300](#) [DC.EXT.8200.0300](#) [DC.CAB.8400.0500](#) [DC.EXT.8610.0100](#) [DC.EXT.4600.0300](#) [AK-ND-C08](#) [AK-ND-C01](#)
[DC.CAB.6201.0200](#) [DC.CAB.8610.0020](#) [DC.CAB.8600.0500](#) [DC.EXT.8200.0500](#) [DC.CAB.8010.0150](#) [DC.EXT.6200.0100](#)
[DC.CAB.8410.0300](#) [DC.EXT.4200.0200](#) [AK-ND-C14](#) [AK-ND-C11](#) [DC.EXT.8610.0500](#)