





**DC Power Cable 2.0m long**  
**Plug 2.1x5.5 mm – straight**  
**Socket 2.1x5.5 mm**  
 flexible, multiwire conductors,  
 stranded of bare copper wires  
**2x0.5mm<sup>2</sup>**



Model
DC Plug (output)
DC Socket (input)
Construction
Cable cross section
Wire diameter
Nominal voltage
Rated current
Length
Jacket
Color
Inner conductor
Insulation resistance
Insulation thickness
Allowable operation temperature
Maximum wire resistance

Model	P21-C21-T050-200BK
DC Plug (output)	<b>2.1x5.5mm, straight</b> (round plug, outer diameter 5.5mm, inner diameter 2.1mm)
DC Socket (input)	<b>2.1x5.5mm, straight</b> (round socket, outer diameter 2.1mm, inner diameter 5.5mm)
Construction	flexible, multiwire conductors, stranded of bare annealed copper wires
Cable cross section	1.7 x 3.6mm
Wire diameter	<b>2x0.50mm<sup>2</sup></b>
Nominal voltage	0-100V
Rated current	1.5A
Length	200cm
Jacket	PVC
Color	Black
Inner conductor	Cu
Insulation resistance	>100MΩ @ 500VDC
Insulation thickness	0.4mm
Allowable operation temperature	-20°C to 70°C
Maximum wire resistance	39.0 Ω/km @ 20°C





## Marking System

model:

**P21-C21-T050-200BK**

1	2	3	4	5	6	7	8			
<b>P</b>	<b>21</b>	<b>-</b>	<b>C</b>	<b>21</b>	<b>-</b>	<b>T</b>	<b>050</b>	<b>-</b>	<b>200</b>	<b>BK</b>

<b>1</b>	<b>Input / Output (side 1)</b>	<p>P - straight plug</p> <p>A - angled plug</p> <p>C - socket</p>
<b>2</b>	<b>Plug / Socket dimensions (side 1)</b>	<p><b>07</b> - 0.7mm / 2.35mm</p> <p><b>13</b> - 1.3mm / 3.5mm</p> <p><b>40</b> - 1.7mm / 4.0mm</p> <p><b>48</b> - 1.7mm / 4.8mm</p> <p><b>55</b> - 1.7mm / 5.5mm</p> <p><b>21</b> - 2.1mm / 5.5mm</p> <p><b>25</b> - 2.5mm / 5.5mm</p>
<b>3</b>	<b>Input / Output (side 2)</b>	<p>P - straight plug</p> <p>A - angled plug</p> <p>C - socket</p>
<b>4</b>	<b>Plug / Socket dimensions (side 2)</b>	<p>T - tinned terminals</p> <p><b>07</b> - 0.7mm / 2.35mm</p> <p><b>13</b> - 1.3mm / 3.5mm</p> <p><b>40</b> - 1.7mm / 4.0mm</p> <p><b>48</b> - 1.7mm / 4.8mm</p> <p><b>55</b> - 1.7mm / 5.5mm</p> <p><b>21</b> - 2.1mm / 5.5mm</p> <p><b>25</b> - 2.5mm / 5.5mm</p>
<b>5</b>	<b>cable type</b>	<p>C- YTLYek (coaxial)</p> <p>T- TLYP</p> <p>O- YTLY</p>
<b>6</b>	<b>wire diameter</b>	<p><b>035</b> - 0.35mm<sup>2</sup></p> <p><b>050</b> - 0.5mm<sup>2</sup></p> <p><b>075</b> - 0.75mm<sup>2</sup></p> <p><b>100</b> - 1.0mm<sup>2</sup></p>
<b>7</b>	<b>length</b>	<p><b>050</b> - 500mm</p> <p><b>200</b> - 2000mm</p>
<b>8</b>	<b>color</b>	<p><b>BK</b> - black</p> <p><b>WH</b> - white</p> <p><b>TR</b> - transparent</p>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [DC Power Cords](#) category:*

*Click to view products by [WEST POL](#) manufacturer:*

Other Similar products are found below :

[2R6006A20A120](#) [172-4000](#) [172-4101](#) [21033836407](#) [2J-1865A](#) [2R7006A20A120](#) [426055400-3](#) [420680840-3](#) [96CB-POWER-B-1.8M2](#)  
[2052KH2-BK](#) [804001P03M050G](#) [2050KH1-BK](#) [216603-0037](#) [862545-5](#) [BXC-10567](#) [172-2555](#) [32102-022800-200-RS](#) [DC.CAB.8000.0300](#)  
[DC.CAB.6400.0200](#) [AK-ND-C07](#) [AK-ND-C16](#) [DC.CAB.4600.0200](#) [DC.CAB.8400.0020](#) [DC.CAB.4201.0150](#) [DC.CAB.8200.0300](#)  
[DC.CAB.6601.0200](#) [DC.CAB.6601.0020](#) [DC.CAB.4201.0200](#) [DC.CAB.8010.0020](#) [AK-ND-C12](#) [AK-ND-C06](#) [DC.EXT.4200.0300](#)  
[DC.EXT.6200.0300](#) [DC.EXT.8200.0300](#) [DC.CAB.8400.0500](#) [DC.EXT.8610.0100](#) [DC.EXT.4600.0300](#) [AK-ND-C08](#) [AK-ND-C01](#)  
[DC.CAB.6201.0200](#) [DC.CAB.8610.0020](#) [DC.CAB.8600.0500](#) [DC.EXT.8200.0500](#) [DC.CAB.8010.0150](#) [DC.EXT.6200.0100](#)  
[DC.CAB.8410.0300](#) [DC.EXT.4200.0200](#) [AK-ND-C14](#) [AK-ND-C11](#) [DC.EXT.8610.0500](#)