





**DC Power Cable 3.0m long**  
**Plug 2.5x5.5 mm – straight**  
**Socket 2.5x5.5 mm**  
 flexible, multiwire conductors,  
 stranded of bare copper wires  
**2x0.5mm<sup>2</sup>**



Model
DC Plug (output)
DC Socket (input)
Construction
Cable cross section
Wire diameter
Nominal voltage
Rated current
Length
Jacket
Color
Inner conductor
Insulation resistance
Insulation thickness
Allowable operation temperature
Maximum wire resistance

Model
<b>P25-C25-T050-300BK</b>
<b>2.5x5.5mm, straight</b> (round plug, outer diameter 5.5mm, inner diameter 2.5mm)
<b>2.5x5.5mm, straight</b> (round socket, outer diameter 2.5mm, inner diameter 5.5mm)
flexible, multiwire conductors, stranded of bare annealed copper wires
1.7 x 3.6mm
<b>2x0.50mm<sup>2</sup></b>
0-100V
1.5A
300cm
PVC
Black
Cu
>100MΩ @ 500VDC
0.4mm
-20°C to 70°C
39.0 Ω/km @ 20°C





## Marking System

model:

**P25-C25-T050-300BK**

1	2	3	4	5	6	7	8			
<b>P</b>	<b>25</b>	<b>-</b>	<b>C</b>	<b>25</b>	<b>-</b>	<b>T</b>	<b>050</b>	<b>-</b>	<b>300</b>	<b>BK</b>

<b>1</b>	<b>Input / Output (side 1)</b>	<p><b>P</b> - straight plug</p> <p><b>A</b> - angled plug</p> <p><b>C</b> - socket</p>
<b>2</b>	<b>Plug / Socket dimensions (side 1)</b>	<p><b>07</b> - 0.7mm / 2.35mm</p> <p><b>13</b> - 1.3mm / 3.5mm</p> <p><b>40</b> - 1.7mm / 4.0mm</p> <p><b>48</b> - 1.7mm / 4.8mm</p> <p><b>55</b> - 1.7mm / 5.5mm</p> <p><b>21</b> - 2.1mm / 5.5mm</p> <p><b>25</b> - 2.5mm / 5.5mm</p>
<b>3</b>	<b>Input / Output (side 2)</b>	<p><b>P</b> - straight plug</p> <p><b>A</b> - angled plug</p> <p><b>C</b> - socket</p>
<b>4</b>	<b>Plug / Socket dimensions (side 2)</b>	<p><b>T</b> - tinned terminals</p> <p><b>07</b> - 0.7mm / 2.35mm</p> <p><b>13</b> - 1.3mm / 3.5mm</p> <p><b>40</b> - 1.7mm / 4.0mm</p> <p><b>48</b> - 1.7mm / 4.8mm</p> <p><b>55</b> - 1.7mm / 5.5mm</p> <p><b>21</b> - 2.1mm / 5.5mm</p> <p><b>25</b> - 2.5mm / 5.5mm</p>
<b>5</b>	<b>cable type</b>	<p><b>C</b> - YTLYek (coaxial)</p> <p><b>T</b> - TLYP</p> <p><b>O</b> - YTLY</p>
<b>6</b>	<b>wire diameter</b>	<p><b>035</b> - 0.35mm<sup>2</sup></p> <p><b>050</b> - 0.5mm<sup>2</sup></p> <p><b>075</b> - 0.75mm<sup>2</sup></p> <p><b>100</b> - 1.0mm<sup>2</sup></p>
<b>7</b>	<b>length</b>	<p><b>200</b> - 2000mm</p> <p><b>300</b> - 3000mm</p>
<b>8</b>	<b>color</b>	<p><b>BK</b> - black</p> <p><b>WH</b> - white</p> <p><b>TR</b> - transparent</p>

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [DC Power Cords](#) category:*

*Click to view products by [WEST POL](#) manufacturer:*

Other Similar products are found below :

[2R6006A20A120](#) [172-4000](#) [172-4101](#) [21033836407](#) [2J-1865A](#) [2R7006A20A120](#) [426055400-3](#) [420680840-3](#) [96CB-POWER-B-1.8M2](#)  
[2052KH2-BK](#) [804001P03M050G](#) [2050KH1-BK](#) [216603-0037](#) [862545-5](#) [BXC-10567](#) [172-2555](#) [32102-022800-200-RS](#) [DC.CAB.8000.0300](#)  
[DC.CAB.6400.0200](#) [AK-ND-C07](#) [AK-ND-C16](#) [DC.CAB.4600.0200](#) [DC.CAB.8400.0020](#) [DC.CAB.4201.0150](#) [DC.CAB.8200.0300](#)  
[DC.CAB.6601.0200](#) [DC.CAB.6601.0020](#) [DC.CAB.4201.0200](#) [DC.CAB.8010.0020](#) [AK-ND-C12](#) [AK-ND-C06](#) [DC.EXT.4200.0300](#)  
[DC.EXT.6200.0300](#) [DC.EXT.8200.0300](#) [DC.CAB.8400.0500](#) [DC.EXT.8610.0100](#) [DC.EXT.4600.0300](#) [AK-ND-C08](#) [AK-ND-C01](#)  
[DC.CAB.6201.0200](#) [DC.CAB.8610.0020](#) [DC.CAB.8600.0500](#) [DC.EXT.8200.0500](#) [DC.CAB.8010.0150](#) [DC.EXT.6200.0100](#)  
[DC.CAB.8410.0300](#) [DC.EXT.4200.0200](#) [AK-ND-C14](#) [AK-ND-C11](#) [DC.EXT.8610.0500](#)