





**DC Power Cable 2m long**  
**Socket 2.5x5.5 mm**  
 flexible, multiwire conductors,  
 stranded of bare copper wires  
**2x0.75mm<sup>2</sup>**



| Model                           | S25-TT-T075-200BK   |
|---------------------------------|---|
| DC Plug (output)                | tinned terminals  |
| DC Socket (input)               | <b>2.5x5.5mm</b> , (round plug, outer diameter 5.5mm, inner diameter 2.5mm) |
| Construction                    | flexible, multiwire conductors, stranded of bare annealed copper wires      |
| Cable cross section             | 2.3 x 4.8mm   |
| Wire diameter                   | <b>2x0.75mm<sup>2</sup></b>   |
| Nominal voltage                 | 0-100V  |
| Rated current                   | 2.3A  |
| Length                          | 200cm   |
| Jacket                          | PVC   |
| Color                           | Black   |
| Inner conductor                 | Cu  |
| Insulation resistance           | >100MΩ @ 500VDC   |
| Insulation thickness            | 0.4mm   |
| Allowable operation temperature | -20°C to 70°C   |
| Maximum wire resistance         | 26 Ω/km @ 20°C  |



## Marking System

model:

**S25-TT-T075-200BK**

| 1 | 2  | 3 | 4   | 5 | 6 | 7   | 8 |     |    |
|---|----|---|-----|---|---|-----|---|-----|----|
| S | 25 | - | T T | - | T | 075 | - | 200 | BK |

|   |                                   |  |
|---|-----------------------------------|--|
| 1 | Input / Output (side 1)           | <p>P - straight plug</p> <p>A - angled plug</p> <p>S - socket</p>  |
| 2 | Plug / Socket dimensions (side 1) | <p>07 - 0.7mm / 2.35mm</p> <p>13 - 1.3mm / 3.5mm</p> <p>40 - 1.7mm / 4.0mm</p> <p>48 - 1.7mm / 4.8mm</p> <p>55 - 1.7mm / 5.5mm</p> <p>21 - 2.1mm / 5.5mm</p> <p>25 - 2.5mm / 5.5mm</p>                             |
| 3 | Input / Output (side 2)           | <p>P - straight plug</p> <p>A - angled plug</p> <p>S - socket</p>  |
| 4 | Plug / Socket dimensions (side 2) | <p>T - tinned terminals</p> <p>07 - 0.7mm / 2.35mm</p> <p>13 - 1.3mm / 3.5mm</p> <p>40 - 1.7mm / 4.0mm</p> <p>48 - 1.7mm / 4.8mm</p> <p>55 - 1.7mm / 5.5mm</p> <p>21 - 2.1mm / 5.5mm</p> <p>25 - 2.5mm / 5.5mm</p> |
| 5 | cable type                        | <p>C- YTLYek (coaxial)</p> <p>T- TLYP</p> <p>O- YTLY</p>   |
| 6 | wire diameter                     | <p>035 - 0.35mm<sup>2</sup></p> <p>050 - 0.5mm<sup>2</sup></p> <p>075 - 0.75mm<sup>2</sup></p> <p>100 - 1.0mm<sup>2</sup></p>  |
| 7 | length                            | <p>025 - 250mm</p> <p>200 - 2000mm</p>   |
| 8 | color                             | <p>BK - black</p> <p>WH - white</p> <p>TR - transparent</p>  |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [DC Power Cords](#) category:*

*Click to view products by [WEST POL](#) manufacturer:*

Other Similar products are found below :

[2R6006A20A120](#) [172-4000](#) [172-4101](#) [21033836407](#) [2J-1865A](#) [2R7006A20A120](#) [426055400-3](#) [420680840-3](#) [96CB-POWER-B-1.8M2](#)  
[2052KH2-BK](#) [804001P03M050G](#) [2050KH1-BK](#) [216603-0037](#) [862545-5](#) [BXC-10567](#) [172-2555](#) [32102-022800-200-RS](#) [DC.CAB.8000.0300](#)  
[DC.CAB.6400.0200](#) [AK-ND-C07](#) [AK-ND-C16](#) [DC.CAB.4600.0200](#) [DC.CAB.8400.0020](#) [DC.CAB.4201.0150](#) [DC.CAB.8200.0300](#)  
[DC.CAB.6601.0200](#) [DC.CAB.6601.0020](#) [DC.CAB.4201.0200](#) [DC.CAB.8010.0020](#) [AK-ND-C12](#) [AK-ND-C06](#) [DC.EXT.4200.0300](#)  
[DC.EXT.6200.0300](#) [DC.EXT.8200.0300](#) [DC.CAB.8400.0500](#) [DC.EXT.8610.0100](#) [DC.EXT.4600.0300](#) [AK-ND-C08](#) [AK-ND-C01](#)  
[DC.CAB.6201.0200](#) [DC.CAB.8610.0020](#) [DC.CAB.8600.0500](#) [DC.EXT.8200.0500](#) [DC.CAB.8010.0150](#) [DC.EXT.6200.0100](#)  
[DC.CAB.8410.0300](#) [DC.EXT.4200.0200](#) [AK-ND-C14](#) [AK-ND-C11](#) [DC.EXT.8610.0500](#)