



TorqueVario®-S ESD Torque Screwdriver Set, 13 pcs.



Handle	Torque infinitely adjustable with Torque-Setter setting tool (also supplied).
	Ergonomic multi-component handle, made of ESD-safe dissipative material.
Standards	DIN EN 61340-5-1/ 61340-5-2.
	EN ISO 6798, BS EN 26789, ASME B107.14M
Accuracy	±6%, traceable to national standards.
Application	For ESD applications where recommended torque settings are important.
Extra	Delivered in robust metal box, incl. factory calibration certificate.

Best.Nr.	ĺ	Brutto	Netto
27687	1		

Best.Nr.	Ð	Nm	=	Ð	*	0	—	⊖‡		• 1		+	=	L ↓ □	۲
04013	4,0		25					0,5							
01624	5,5		25					0,8							
26866		0,8-2,0				4			131			30			
01657			25	PH1											
01688			25		PZ1										
27711						1/4				4			162	11	
27279							40				150				
05298			25	PH0											
05300			25		PZ0										
01713			25												T7
01714			25												T8
01715			25												Т9
01716			25												T10



Z 36 0 04

Needle Nose Pliers Professional ESD.



Standards	DIN ISO 9655.
Head shape	Straight head.
Design	Fine, semi-circular tips.
	Smooth gripping surfaces.
	With opening spring.
Material	C 45 Special tool steel, hardened and tempered.
Application	Mainly for precision gripping and bending work.

Best.Nr.	₩mm	₩	A	В	D	F	•••	-	Brutto	Netto
26799	120	4 ¾	9,5	23	6,5	1,4	60	5		
27905	145	5 ¾	12,0	40	7,5	2,0	93	5		



Z 38 0 04

Flat Nose Pliers Professional ESD.



Standards	DIN ISO 9655.
Head shape	Flat, short jaws.
Design	Smooth gripping surfaces.
	With opening spring.
Material	C 45 Special tool steel, hardened and tempered.
Application	Mainly for precision gripping and bending work.

Best.Nr.	€mm	t ₩	÷÷		Brutto	Netto
26806	120	4 ¾	60	5		



Z 41 3 04

Diagonal Cutter Professional ESD.



DIN ISO 9654.
Wide, pointed head.
Cutting edge without bevel for absolute flush cutting.
Maximum service life of cutting edge achieved through additional inductive
hardening to approx. 64 HRC.
With opening spring.
High alloy carbon steel C 60.
For absolutely flush cutting of copper wire.
)

Best.Nr.	₩mm	₩	0	÷	-	Brutto	Netto
26821	115	4 1⁄2	1,0	60	5		



Z 44 1 04

Diagonal Cutter Professional ESD.



Standards	DIN ISO 9654.
Head shape	Wide, semi-circular head.
Design	Bevelled cutting edges, also appropriate for thin, hard wires.
	Maximum service life of cutting edge achieved through additional inductive
	hardening to approx. 64 HRC.
	With opening spring.
Material	High alloy carbon steel C 60.
Application	All round electronic diagonal cutter for cutting wires of different hardnesses.

Best.Nr.	₩mm	₩	0	0	0			Brutto	Netto
26831	115	4 1/2	1,4	1,0	0,4	60	5		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for wiha manufacturer:

Other Similar products are found below :

56818	00573	01030	75802	21248	26307	27302	27835	28050	28084	28390	28501	28507	26113	26539	26626	26629	26804	28522
28882	32573	32705	32712	32752	32954	34700	36268	36791	38043	43618	44506	54095	31705	31890	32090	32093	32714	32793
37225	39104	41106	44503	45811	46796	66991	74586	74732	27235	28551	23490							