

2882S10



Wiha. Premium Werkzeuge für Profis.

TorqueVario®-S ESD Torque Screwdriver Set, 13 pcs.



Handle Torque infinitely adjustable with Torque-Setter setting tool (also supplied). Ergonomic multi-component handle, made of ESD-safe dissipative material.

Standards DIN EN 61340-5-1/ 61340-5-2. EN ISO 6798, BS EN 26789, ASME B107.14M

Accuracy ±6%, traceable to national standards.

Application For ESD applications where recommended torque settings are important.

Extra Delivered in robust metal box, incl. factory calibration certificate.

Best.Nr.		Brutto	Netto
27687	1		

Best.Nr.	⌀	Nm													
04013	4,0		25				0,5								
01624	5,5		25				0,8								
26866		0,8-2,0				4		131			30				
01657			25	PH1											
01688			25		PZ1										
27711						1/4			4			162	11		
27279						40				150					
05298			25	PH0											
05300			25		PZ0										
01713			25												T7
01714			25												T8
01715			25												T9
01716			25												T10



Wiha. Premium Werkzeuge
für Profis.

Z 36 0 04

Needle Nose Pliers Professional ESD.



Standards DIN ISO 9655.
Head shape Straight head.
Design Fine, semi-circular tips.
 Smooth gripping surfaces.
 With opening spring.
Material C 45 Special tool steel, hardened and tempered.
Application Mainly for precision gripping and bending work.

Best.Nr.	↔ mm	↔ in	A	B	D	F	↕	↕	Brutto	Netto
26799	120	4 ¾	9,5	23	6,5	1,4	60	5		
27905	145	5 ¾	12,0	40	7,5	2,0	93	5		







Wiha. Premium Werkzeuge
für Profis.

Z 38 0 04

Flat Nose Pliers Professional ESD.



Standards DIN ISO 9655.
Head shape Flat, short jaws.
Design Smooth gripping surfaces.
 With opening spring.
Material C 45 Special tool steel, hardened and tempered.
Application Mainly for precision gripping and bending work.

Best.Nr.					Brutto	Netto
26806	120	4 3/4	60	5		



Wiha. Premium Werkzeuge
für Profis.

Z 41 3 04

Diagonal Cutter Professional ESD.



Standards DIN ISO 9654.
Head shape Wide, pointed head.
Design Cutting edge without bevel for absolute flush cutting.
 Maximum service life of cutting edge achieved through additional inductive
 hardening to approx. 64 HRC.
 With opening spring.
Material High alloy carbon steel C 60.
Application For absolutely flush cutting of copper wire.

Best.Nr.	↔ mm	↔ in	○	⚖	▬	Brutto	Netto
26821	115	4 ½	1,0	60	5		

Z 44 1 04

Diagonal Cutter Professional ESD.



Standards DIN ISO 9654.
 Head shape Wide, semi-circular head.
 Design Bevelled cutting edges, also appropriate for thin, hard wires.
 Maximum service life of cutting edge achieved through additional inductive
 hardening to approx. 64 HRC.
 With opening spring.
 Material High alloy carbon steel C 60.
 Application All round electronic diagonal cutter for cutting wires of different hardnesses.

Best.Nr.	↔ mm	↔ in	○	○	●	↔	↔	Brutto	Netto
26831	115	4 ½	1,4	1,0	0,4	60	5		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Wiha](#) manufacturer:

Other Similar products are found below :

[28310](#) [28016](#) [56818](#) [00573](#) [01030](#) [00880](#) [21248](#) [26307](#) [92191](#) [26815](#) [28050](#) [28084](#) [28501](#) [28507](#) [26092](#) [26113](#) [26550](#) [26629](#) [26802](#)
[28522](#) [30292](#) [32573](#) [32613](#) [32705](#) [32712](#) [32752](#) [32954](#) [33478](#) [36268](#) [43618](#) [44506](#) [45824](#) [31705](#) [56801](#) [32188](#) [32714](#) [32793](#) [32870](#)
[33969](#) [33971](#) [36995](#) [44521](#) [45811](#) [66991](#) [74586](#) [74732](#) [26491](#) [26490](#) [28551](#) [23490](#)