

Torque screwdriver set TorqueVario®-S ESD



0,4-1,0 Nm assorted, variably adjustable torque limit, 14-pcs. incl. box

2882S13

Order-No.	Icon	Description
43898		1
		1 x Torque screwdriver TorqueVario®-S ESD variably adjustable torque limit
		1 x Bit holder clamping with ball for torque screwdriver with long handle
		1 x Setting tool for torque screwdriver with long handle
		1 x PH0 / 1 x PH1
		1 x PZ0 / 1 x PZ1
		1 x T4 / 1 x T5 / 1 x T6 / 1 x T8
		1 x Box

DIN EN ISO 6789.
IEC 61340-5-1.

Torque screwdriver TorqueVario®-S ESD



variably adjustable torque limit


2882

Order-No.	Nm	Accuracy	Bit	Length	Weight	Box
36851	0.04 - 0.46	10 %	4.0	127	23	1
26865	0.1 - 0.6	10 %	4.0	127	23	1
36852	0.1 - 0.6	6 %	4.0	127	23	1
26629	0.4 - 1	6 %	4.0	127	23	1
26866	0.5 - 2	6 %	4.0	131	30	1
30495	0.8 - 5	6 %	4.0	138	36	1

• Precision in range of 0.1-0.46 Nm.
IEC 61340-5-1. DIN EN ISO 6789.



INFOBOX:
**Electrostatic
conductive ESD tools**



- Dissipative tools by Wiha discharge the electrostatic energy in a controlled, safe manner.
- ESD tools meet the ESD Standard IEC 61340-5-1.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Screwdrivers, Nut Drivers & Socket Drivers](#) category:

Click to view products by [Wiha Tools USA](#) manufacturer:

Other Similar products are found below :

[1406504-2](#) [272012M](#) [271001M](#) [30246](#) [HMM-HH](#) [32024](#) [TL10416](#) [612020B](#) [35-045](#) [6951](#) [83](#) [9977](#) [EMF](#) [99833](#) [RB1](#) [S3166V](#) [X103V](#)
[XTD10TP](#) [X108N](#) [HS7N](#) [HS618N](#) [LN25MMN](#) [HS18N](#) [P4N](#) [R146N](#) [P12SN](#) [R5324N](#) [99764N](#) [P8N](#) [99312N](#) [R3163N](#) [SX101N](#) [LN22N](#)
[XTD10N](#) [9955MMN](#) [995MMN](#) [996MMN](#) [LN25N](#) [THS9N](#) [R3166N](#) [R144N](#) [RB2N](#) [HS10N](#) [99964BPN](#) [HS11N](#) [HS12N](#) [THS8N](#) [TL12N](#)
[R5168N](#) [600VN](#)