

SOT-23 Plastic-Encapsulate Transistors




MMBT2222A

Features

- Complementary to MMBT2907A

SOT-23



1. BASE
2. EMITTER
3. COLLECTOR

MAXIMUM RATINGS ($T_a=25^\circ\text{C}$ unless otherwise noted)

| Symbol | Parameter | Value | Unit |
|-----------------|---|----------|---------------------------|
| V_{CB0} | Collector-Base Voltage | 75 | V |
| V_{CE0} | Collector-Emitter Voltage | 40 | V |
| V_{EB0} | Emitter-Base Voltage | 6 | V |
| I_C | Collector Current -Continuous | 600 | mA |
| P_C | Collector Dissipation | 300 | mW |
| $R_{\theta JA}$ | Thermal Resistance, Junction to Ambient | 417 | $^\circ\text{C}/\text{W}$ |
| T_J | Junction Temperature | 150 | $^\circ\text{C}$ |
| T_{stg} | Storage Temperature | -55~+150 | $^\circ\text{C}$ |









ELECTRICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$ unless otherwise specified)

| Parameter | Symbol | Test conditions | Min | Typ | Max | Unit |
|--------------------------------------|-----------------|--|-----|-----|------------|---------------|
| Collector-base breakdown voltage | $V_{(BR)CBO}$ | $I_C = 10\mu\text{A}, I_E = 0$ | 75 | | | V |
| Collector-emitter breakdown voltage | $V_{(BR)CEO}^*$ | $I_C = 10\text{mA}, I_B = 0$ | 40 | | | V |
| Emitter-base breakdown voltage | $V_{(BR)EBO}$ | $I_E = 10\mu\text{A}, I_C = 0$ | 6 | | | V |
| Collector cut-off current | I_{CBO} | $V_{CB} = 60\text{V}, I_E = 0$ | | | 0.01 | μA |
| Collector cut-off current | I_{CEX} | $V_{CE} = 30\text{V}, V_{BE(off)} = 3\text{V}$ | | | 0.01 | μA |
| Emitter cut-off current | I_{EBO} | $V_{EB} = 3\text{V}, I_C = 0$ | | | 0.1 | μA |
| DC current gain | $h_{FE(1)}^*$ | $V_{CE} = 10\text{V}, I_C = 150\text{mA}$ | 100 | | 300 | |
| | $h_{FE(2)}$ | $V_{CE} = 10\text{V}, I_C = 0.1\text{mA}$ | 40 | | | |
| | $h_{FE(3)}^*$ | $V_{CE} = 10\text{V}, I_C = 500\text{mA}$ | 42 | | | |
| Collector-emitter saturation voltage | $V_{CE(sat)}^*$ | $I_C = 500\text{mA}, I_B = 50\text{mA}$ $I_C = 150\text{mA}, I_B = 15\text{mA}$ | | | 1 0.3 | V |
| Base-emitter saturation voltage | $V_{BE(sat)}^*$ | $I_C = 500\text{mA}, I_B = 50\text{mA}$ $I_C = 150\text{mA}, I_B = 15\text{mA}$ | | | 2.0 1.2 | V |
| Transition frequency | f_T | $V_{CE} = 20\text{V}, I_C = 20\text{mA}, f = 100\text{MHz}$ | 300 | | | MHz |
| Delay time | t_d | $V_{CC} = 30\text{V}, V_{BE(off)} = -0.5\text{V}$ | | | 10 | ns |
| Rise time | t_r | $I_C = 150\text{mA}, I_{B1} = 15\text{mA}$ | | | 25 | ns |
| Storage time | t_s | $V_{CC} = 30\text{V}, I_C = 150\text{mA}$ | | | 225 | ns |
| Fall time | t_f | $I_{B1} = -I_{B2} = 15\text{mA}$ | | | 60 | ns |

*pulse test: Pulse Width $\leq 300\mu\text{s}$, Duty Cycles $\leq 2.0\%$.



Typical Characteristics

SOT-23 Plastic-Encapsulate Transistors




SOT-23 Plastic-Encapsulate Transistors

SOT-23 Package Outline Dimensions



| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|--------|---------------------------|-------|----------------------|-------|
| | Min | Max | Min | Max |
| A | 0.900 | 1.150 | 0.035 | 0.045 |
| A1 | 0.000 | 0.100 | 0.000 | 0.004 |
| A2 | 0.900 | 1.050 | 0.035 | 0.041 |
| b | 0.300 | 0.500 | 0.012 | 0.020 |
| c | 0.080 | 0.150 | 0.003 | 0.006 |
| D | 2.800 | 3.000 | 0.110 | 0.118 |
| E | 1.200 | 1.400 | 0.047 | 0.055 |
| E1 | 2.250 | 2.550 | 0.089 | 0.100 |
| e | 0.950 TYP | | 0.037 TYP | |
| e1 | 1.800 | 2.000 | 0.071 | 0.079 |
| L | 0.550 REF | | 0.022 REF | |
| L1 | 0.300 | 0.500 | 0.012 | 0.020 |
| θ | 0° | 8° | 0° | 8° |

SOT-23 Suggested Pad Layout



Note:

1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

NOTICE

JCET reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JCET does not assume any liability arising out of the application or use of any product described herein.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Bipolar Transistors - BJT category](#):

Click to view products by [Wild Goose manufacturer](#):

Other Similar products are found below :

[BC559C](#) [MCH4017-TL-H](#) [MMBT-2369-TR](#) [BC546/116](#) [NJVMJD148T4G](#) [NTE16](#) [NTE195A](#) [IMX9T110](#) [2N4401-A](#) [2N6728](#) [2SA1419T-TD-H](#) [2SB1204S-TL-E](#) [2SC5488A-TL-H](#) [FMC5AT148](#) [2N2369ADCSM](#) [2N2907A](#) [2N3904-NS](#) [2N5769](#) [2SC4618TLN](#) [CPH6501-TL-E](#) [US6T6TR](#) [BAX18/A52R](#) [BC556/112](#) [IMZ2AT108](#) [MMST8098T146](#) [MCH6102-TL-E](#) [BC846B-13-F](#) [2N3879](#) [30A02MH-TL-E](#) [NTE13](#) [NTE282](#) [NTE323](#) [NTE350](#) [NTE81](#) [JANTX2N2920L](#) [JANSR2N2907AUB](#) [CMLT3946EG TR](#) [SNSS40600CF8T1G](#) [CMLT3906EG TR](#) [GRP-DATA-JANS2N2907AUB](#) [GRP-DATA-JANS2N2222AUA](#) [MMDT3946FL3-7](#) [2N4240](#) [JANS2N3019](#) [MSB30KH-13](#) [2N2221AUB](#) [2SD1815T-TL-E](#) [2N6678](#) [2N2907Ae4](#) [JAN2N3507](#)