


WS7916S

CMOS High Gain GPS LNA

<http://www.sh-willsemi.com>

Descriptions

The WS7916S is a low noise amplifier (LNA) for GNSS receiver applications (including GPS, GLONASS, BeiDou and Galileo), available in a small 6-pin DFN package. The WS7916S requires only one external inductor for input matching.




DFN1510-6L (Bottom view)


The WS7916S is designed to achieve low power dissipation and good performance.

Features

- Operating frequency: 1550 MHz to 1615 MHz
- Noise figure = 0.65 dB
- Gain = 16.5 dB
- Input 1 dB compression point = -5.5 dBm
- Out-of-band input IP3 = +8.0 dBm
- Supply voltage: 1.8 V to 3.1 V
- Integrated supply decoupling capacitor
- Digital On/Off switch (1.2 V logic high level)
- Supply current: 6.9 mA
- Power-down mode leakage current < 3 μ A
- One external matching inductor required
- RF output internally matched to 50 Ohm
- ESD protection: HBM > 2.0kV for all pins
- Package: 6-pin DFN, 1.5 x 1.0 x 0.55 mm³
- Process: CMOS



Pin configuration (Top view)



S = Device code
* = Month code (A~Z)

Marking (Top view)

Applications

- Cell phones
- Tablets
- Other RF front-end modules


Order information

Device	Package	Shipping
WS7916S-6/TR	DFN1510-6L	3000/Reel&Tape

Pinning Information

Pin	Description	Transparent top view	Symbol view
1	GNDRF		
2	GND		
3	RFIN		
4	VDD		
5	EN		
6	RFOUT		

Application Information



Symbol	Description	Footprint	Value	Supplier	Comment
U1	WS7916S	1.5x1.0x0.55 mm ³	N/A	Will-Semi	DUT
C1	Capacitor	0402	1 nF	Various	DC blocking
C2	Capacitor	0402	1 nF	Various	Supply decoupling
L1	Inductor	0402	10 nH	Murata LQW15	Input matching

Quick Reference Data

Freq = 1575.42 MHz; V_{CC} = 2.8 V; $V_{EN} > 1.2$ V; Temp = 25°C; input matched to 50 Ω with a 10 nH inductor. The condition is applied unless otherwise specified.

Symbol	Parameter	Condition	Min	Typ	Max	Unit
V_{CC}	Supply voltage		1.8	2.8	3.1	V
I_{CC}	Supply current			6.9		mA
G_p	Power gain			16.5		dB
NF	Noise figure			0.65		dB
IP_{1dB}	Input power at 1 dB gain compression			-5.5		dBm
IIP_3	Input third-order intercept point			+8.0		dBm

Recommended Operating Conditions

Symbol	Parameter	Condition	Min	Typ	Max	Unit
V_{CC}	Supply voltage		1.8		3.1	V
Temp	Ambient temperature		-40	+25	+85	°C
V_{EN}	Input voltage on pin 6 (EN)	OFF state		0	0.4	V
		ON state	1.2	V_{CC}		V

Absolute Maximum Ratings

Maximum ratings are absolute ratings, exceeding only one of these values may cause irreversible damage to the integrated circuit.

Symbol	Parameter	Condition	Min	Max	Unit
V_{CC}	Supply voltage		-0.3	3.1	V
V_{EN}	Input voltage on pin EN		-0.3	3.1	V
V_{RFIN}	Input voltage on pin RFIN		-0.3	3.1	V
V_{RFOUT}	Input voltage on pin RFOUT		-0.3	3.1	V
P_{in}	RF input power			0	dBm
T_{STG}	Storage temperature		-65	+150	°C
T_J	Junction temperature			150	°C
V_{ESD}	ESD capability all pins	Human Body Model (HBM)		±2000	V

Electrical Characteristics

$1550 \text{ MHz} \leq f \leq 1615 \text{ MHz}$; $V_{CC} = 2.8 \text{ V}$; $V_{EN} > 1.2 \text{ V}$; Temp = 25°C ; input matched to 50Ω with a 10 nH inductor; The condition is applied unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
I_{CC}	Supply current	On state		6.9		mA
		Off state			3	μA
G_p	Power gain	$f = 1575 \text{ MHz}$		16.5		dB
RL_{in}	Input return loss	$f = 1575 \text{ MHz}$		8		dB
RL_{out}	Output return loss	$f = 1575 \text{ MHz}$		13.0		dB
ISL	Reverse isolation	$f = 1575 \text{ MHz}$		24.0		dB
NF	Noise figure ^[1]	$f = 1575 \text{ MHz}$		0.65		dB
$IP_{1\text{dB}}$	Input power at 1 dB gain compression	$f = 1575 \text{ MHz}$		-5.5		dBm
O-IIP ₃	Out-of-band Input third-order intercept point ^[2]			+8.0		dBm
K	Rollett stability factor ^[3]		1			
t_{on}	Turn-on time			5		μs
t_{off}	Turn-off time			5		μs


$1550 \text{ MHz} \leq f \leq 1615 \text{ MHz}$; $V_{CC} = 1.8 \text{ V}$; $V_{EN} > 1.2 \text{ V}$; Temp = 25°C ; input matched to 50Ω with a 10 nH inductor; The condition is applied unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
I_{CC}	Supply current	On state		5		mA
		Off state			3	μA
G_p	Power gain	$f = 1575 \text{ MHz}$		15.5		dB
RL_{in}	Input return loss	$f = 1575 \text{ MHz}$		7.5		dB
RL_{out}	Output return loss	$f = 1575 \text{ MHz}$		13.0		dB
ISL	Reverse isolation	$f = 1575 \text{ MHz}$		24.0		dB
NF	Noise figure ^[1]	$f = 1575 \text{ MHz}$		0.7		dB
$IP_{1\text{dB}}$	Input power at 1 dB gain compression	$f = 1575 \text{ MHz}$		-9.0		dBm
O-IIP ₃	Out-of-band Input third-order intercept point ^[2]			+8.0		dBm
K	Rollett stability factor ^[3]		1			
t_{on}	Turn-on time			5		μs
t_{off}	Turn-off time			5		μs





[1] Including PCB loss (PCB loss: 0.05-0.1 dB @ 1.575 GHz)

[2] $f_1 = 1713 \text{ MHz}$, $f_2 = 1851 \text{ MHz}$, $P_{in} = -20 \text{ dBm}$

[3] 10M~20GHz

Package Outline Dimensions
DFN1510-6L


Symbol	Dimensions In Millimeters		
	Min.	Typ.	Max.
A	0.50	N/A	0.60
A1	0.00	0.02	0.05
A3	0.10REF		
b	0.15	0.20	0.25
D	0.90	1.00	1.10
E	1.40	1.50	1.60
e	0.40	0.50	0.60
H	0.10REF		
L	0.30	0.35	0.40
L1	0.35	0.40	0.45

TAPE AND REEL INFORMATION
Reel Dimensions

Tape Dimensions

Quadrant Assignments For PIN1 Orientation In Tape


RD	Reel Dimension	<input checked="" type="checkbox"/> 7inch <input type="checkbox"/> 13inch
W	Overall width of the carrier tape	<input checked="" type="checkbox"/> 8mm <input type="checkbox"/> 12mm <input type="checkbox"/> 16mm
P1	Pitch between successive cavity centers	<input checked="" type="checkbox"/> 2mm <input checked="" type="checkbox"/> 4mm <input type="checkbox"/> 8mm
Pin1	Pin1 Quadrant	<input checked="" type="checkbox"/> Q1 <input type="checkbox"/> Q2 <input type="checkbox"/> Q3 <input type="checkbox"/> Q4

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Operational Amplifiers - Op Amps category:

Click to view products by Will Semiconductor manufacturer:

Other Similar products are found below :

[OPA2991IDSGR](#) [OPA607IDCKT](#) [007614D](#) [633773R](#) [635798C](#) [635801A](#) [702115D](#) [709228FB](#) [741528D](#) [NCV33072ADR2G](#)
[SC2902DTBR2G](#) [SC2903DR2G](#) [SC2903VDR2G](#) [LM258AYDT](#) [LM358SNG](#) [430227FB](#) [430228DB](#) [460932C](#) [AZV831KTR-G1](#) [409256CB](#)
[430232AB](#) [LM2904DR2GH](#) [LM358YDT](#) [LT1678IS8](#) [042225DB](#) [058184EB](#) [070530X](#) [SC224DR2G](#) [SC239DR2G](#) [SC2902DG](#)
[SCYA5230DR2G](#) [714228XB](#) [714846BB](#) [873836HB](#) [MIC918YC5-TR](#) [TS912BIYDT](#) [NCS2004MUTAG](#) [NCV33202DMR2G](#)
[M38510/13101BPA](#) [NTE925](#) [SC2904DR2G](#) [SC358DR2G](#) [LM358EDR2G](#) [AZV358MTR-G1](#) [AP4310AUMTR-AG1](#) [HA1630D02MMEL-E](#)
[NJM358CG-TE2](#) [HA1630S01LPEL-E](#) [LM324AWPT](#) [HA1630Q06TELL-E](#)