

Description

The WSD75N12GDN56 uses Super Trench technology that is uniquely optimized to provide the most efficient high frequency switching performance. Both conduction and switching power losses are minimized due to an extremely low combination of $R_{DS(on)}$ and Q_g . This device is ideal for high-frequency switching and synchronous rectification.

General Features

- Excellent gate charge x $R_{DS(on)}$ product(FOM)
- Very low on-resistance $R_{DS(on)}$
- 150 °C operating temperature
- Pb-free lead plating
- 100% UIS tested


Product Summary

BV_{DSS}	$R_{DS(on)}$	I_D
120V	6.0m Ω	75A

Application

- DC/DC Converter
- Load switch.

DFN5X6-8 Pin Configuration



Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DSS}	Drain-to-Source Voltage	120	V
V_{GS}	Gate-to-Source Voltage	± 20	V
I_D	Continuous Drain Current ¹ ($T_c=25^\circ\text{C}$)	75	A
I_D	Continuous Drain Current ¹ ($T_c=70^\circ\text{C}$)	70	A
I_{DM}	Pulsed Drain Current	320	A
IAR	Single pulse avalanche current	40	A
E_{ASa}	Single pulse avalanche energy	240	mJ
P_D	Power Dissipation	125	W
T_J, T_{stg}	Operating Junction and Storage Temperature Range	-55 to 150	$^\circ\text{C}$
T_L	Maximum Temperature for Soldering	260	$^\circ\text{C}$
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	1.0	$^\circ\text{C/W}$
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	50	$^\circ\text{C/W}$

Electrical Characteristics (T_J=25°C, unless otherwise noted)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V _{DSS}	Drain to Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	120	--	--	V
I _{DSS}	Drain to Source Leakage Current	V _{DS} = 120V, V _{GS} = 0V	--	--	1	μA
I _{GSS(F)}	Gate to Source Forward Leakage	V _{GS} =+20V	--	--	100	nA
I _{GSS(R)}	Gate to Source Reverse Leakage	V _{GS} =-20V	--	--	-100	nA
V _{GS(TH)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D = 250μA	2.5	3.0	3.5	V
R _{DS(ON)1}	Drain-to-Source On-Resistance	V _{GS} =10V, I _D =20A	--	6.0	6.8	mΩ
g _{FS}	Forward Transconductance	V _{DS} =5V, I _D =50A		130	--	S
C _{iss}	Input Capacitance	V _{GS} = 0V V _{DS} = 50V f = 1.0MHz	--	4282	--	pF
C _{oss}	Output Capacitance		--	429	--	pF
C _{rss}	Reverse Transfer Capacitance		--	17	--	pF
R _g	Gate resistance		--	2.5	--	Ω
t _{d(ON)}	Turn-on Delay Time	I _D =20A V _{DS} = 50V V _{GS} = 10V R _G = 5Ω	--	20	--	ns
t _r	Rise Time		--	11	--	ns
t _{d(OFF)}	Turn-Off Delay Time		--	55	--	ns
t _f	Fall Time		--	28	--	ns
Q _g	Total Gate Charge	V _{GS} =0~10V V _{DS} = 50V I _D =20A	--	61.4	--	nC
Q _{gs}	Gate Source Charge		--	17.4	--	nC
Q _{gd}	Gate Drain Charge		--	14.1	--	nC
I _S	Diode Forward Current	T _C =25 °C	--	--	100	A
I _{SM}	Diode Pulse Current		--	--	320	A
V _{SD}	Diode Forward Voltage	I _S =6.0A, V _{GS} =0V	--	--	1.2	V
t _{rr}	Reverse Recovery time	I _S =20A, V _{DD} =50V dI _F /dt=100A/μs	--	100	--	ns
Q _{rr}	Reverse Recovery Charge		--	250	--	nC

Note :

- 1、 The data tested by surface mounted on a 1 inch 2 FR-4 board with 2OZ copper.
- 2、 The data tested by pulsed , pulse width ≦ 300us , duty cycle ≦ 2%
- 3、 The EAS data shows Max. rating . The test condition is V_{DD}=50V, L=0.3mH, R_g=25Ω, Starting T_J=25 °C
- 4、 The power dissipation is limited by 150°C junction temperature

Typical Electrical and Thermal Characteristics




Figure1: output characteristics




Figure2: Typical drain-source on resistance




Figure3: transfer characteristics




Figure4: forward transconductance




Figure5: Drain-source on-state resistance




Figure6: Typ. capacitances




Figure7: Typ. gate charge




Figure8: Drain-source breakdown voltage




Figure9: Safe operating area




Figure10: Max. transient thermal impedance



Attention

- 1, Any and all Winsok power products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your Winsok power representative nearest you before using any Winsok power products described or contained herein in such applications.
- 2, Winsok power assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all Winsok power products described or contained herein.
- 3, Specifications of any and all Winsok power products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- 4, Winsok power Semiconductor CO., LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- 5, In the event that any or all Winsok power products (including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- 6, No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of Winsok power Semiconductor CO., LTD.
- 7, Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. Winsok power believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- 8, Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the Winsok power product that you intend to use.
- 9, this catalog provides information as of Sep. 2014. Specifications and information herein are subject to change without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [MOSFET](#) category:

Click to view products by [Winsok](#) manufacturer:

Other Similar products are found below :

[614233C](#) [648584F](#) [MCH3443-TL-E](#) [MCH6422-TL-E](#) [NTNS3A92PZT5G](#) [IRFD120](#) [IRFF430](#) [JANTX2N5237](#) [2N7000](#) [AOD464](#)
[2SK2267\(Q\)](#) [2SK2545\(Q,T\)](#) [405094E](#) [423220D](#) [MIC4420CM-TR](#) [VN1206L](#) [614234A](#) [715780A](#) [SSM6J414TU,LF\(T](#) [751625C](#)
[IPS70R2K0CEAKMA1](#) [BSF024N03LT3 G](#) [PSMN4R2-30MLD](#) [TK31J60W5,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#)
[EFC2J004NUZTDG](#) [FCAB21350L1](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE2384](#) [NTE2969](#) [NTE6400A](#) [DMC2700UDMQ-7](#)
[DMN2080UCB4-7](#) [DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [SSM6P54TU,LF](#) [DMP22D4UFO-7B](#) [IPS60R3K4CEAKMA1](#)
[DMN1006UCA6-7](#) [DMN16M9UCA6-7](#) [STF5N65M6](#) [IRF40H233XTMA1](#) [IPSA70R950CEAKMA1](#) [IPSA70R2K0CEAKMA1](#) [STU5N65M6](#)
[C3M0021120D](#) [DMN6022SSD-13](#)