


FEATURES

- $BV_{DSS}=650\text{ V}$, $I_D=47\text{A}$
- $R_{DS(on)}: 0.092\Omega$ (Max) @ $V_{GS}=10\text{V}$
- Very low FOM $R_{DS(on)} \times Q_g$
- 100% avalanche tested
- RoHS compliant
- Ultra-fast body diode
- Very high commutation ruggedness



APPLICATIONS

- Switch Mode Power Supply (SMPS)
- Uninterruptible Power Supply (UPS)
- Power Factor Correction (PFC)

RoHS

Device Marking and Package Information

Device	Package	Marking
WTM47N65FMP	TO-247	47N65FMP XXX YYWW

Absolute Maximum Ratings $T_C = 25^\circ\text{C}$, unless otherwise noted

Parameter	Symbol	Value	Unit
Drain-Source Voltage ($V_{GS} = 0\text{V}$)	V_{DSS}	650	V
Continuous Drain Current	I_D	47	A
Pulsed Drain Current (note1)	I_{DM}	141	A
Gate-Source Voltage	V_{GSS}	± 30	V
Single Pulse Avalanche Energy (note2)	E_{AS}	1280	mJ
Avalanche Current (note1)	I_{AR}	10.5	A
Repetitive Avalanche Energy (note1)	E_{AR}	1.7	mJ
MOSFET dv/dt ruggedness, $V_{DS}=0\dots 400\text{ V}$	dv/dt	50	V/ns
Reverse diode dv/dt, $V_{DS}=0\dots 400\text{ V}$, $I_{SD} \leq I_D$	dv/dt	50	V/ns
Power Dissipation ($T_C = 25^\circ\text{C}$)	P_D	391	W
Operating Junction and Storage Temperature Range	T_J , T_{stg}	-55~+150	°C

Thermal Resistance

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Case, Max.	R_{thJC}	0.32	K/W
Thermal Resistance, Junction-to-Ambient, Max.	R_{thJA}	62	

Specifications $T_J = 25^\circ\text{C}$, unless otherwise noted

Parameter	Symbol	Test Conditions	Value			Unit
			Min.	Typ.	Max.	
Static						
Drain-Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	$V_{\text{GS}} = 0\text{V}, I_D = 250\mu\text{A}$	600	--	--	V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{\text{DS}} = 650\text{V}, V_{\text{GS}} = 0\text{V}, T_J = 25^\circ\text{C}$	--	--	5	μA
		$V_{\text{DS}} = 650\text{V}, V_{\text{GS}} = 0\text{V}, T_J = 150^\circ\text{C}$	--	--	1000	
Gate-Source Leakage	I_{GSS}	$V_{\text{GS}} = \pm 30\text{V}$	--	--	± 100	nA
Gate-Source Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{DS}} = V_{\text{GS}}, I_D = 0.25\text{mA}$	3.0	--	5.0	V
Drain-Source On-Resistance (Note3)	$R_{\text{DS}(\text{on})}$	$V_{\text{GS}} = 10\text{V}, I_D = 23.5\text{A}$	--	0.080	0.092	Ω
Gate Resistance	R_G	$f = 1.0\text{MHz}$, open drain	--	1.95	--	Ω
Dynamic						
Input Capacitance	C_{iss}	$V_{\text{GS}} = 0\text{V}, V_{\text{DS}} = 50\text{V}, f = 1.0\text{MHz}$	--	3680	--	pF
Output Capacitance	C_{oss}		--	390	--	
Reverse Transfer Capacitance	C_{rss}		--	15	--	
Effective output capacitance, energy related	$C_{\text{o(er)}}$	$V_{\text{GS}}=0\text{V}, V_{\text{DS}}=0\ldots 400\text{V}$	--	131	--	
Effective output capacitance, time related	$C_{\text{o(tr)}}$	$I_D=\text{constant}, V_{\text{GS}}=0\text{V}, V_{\text{DS}}=0\ldots 400\text{V}$	--	675	--	
Total Gate Charge	Q_g	$V_{\text{DD}} = 480\text{V}, I_D = 47\text{A}, V_{\text{GS}} = 10\text{V}$	--	72	--	nC
Gate-Source Charge	Q_{gs}		--	14	--	
Gate-Drain Charge	Q_{gd}		--	24	--	
Turn-on Delay Time	$t_{\text{d(on)}}$	$V_{\text{DD}} = 400\text{V}, I_D = 25.8\text{A}, V_{\text{GS}} = 10\text{V}, R_G = 1.9\Omega$	--	15	--	ns
Turn-on Rise Time	t_r		--	12	--	
Turn-off Delay Time	$t_{\text{d(off)}}$		--	80	--	
Turn-off Fall Time	t_f		--	6	--	
Drain-Source Body Diode Characteristics						
Continuous Body Diode Current	I_S	$T_C = 25^\circ\text{C}$	--	--	47	A
Pulsed Diode Forward Current	I_{SM}		--	--	141	
Body Diode Voltage	V_{SD}	$T_J = 25^\circ\text{C}, I_{\text{SD}} = 47\text{A}, V_{\text{GS}} = 0\text{V}$	--	0.9	1.2	V
Reverse Recovery Time	t_{rr}	$V_R = 400\text{V}, I_F = 47\text{A}, dI_F/dt = 100\text{A}/\mu\text{s}$	--	140	--	μC
Reverse Recovery Charge	Q_{rr}		--	0.7	--	
Peak Reverse Recovery Current	I_{rrm}		--	11	--	

Notes

- Repetitive Rating: Pulse width limited by maximum junction temperature
- $I_{\text{AS}} = 10.5\text{A}, V_{\text{DD}} = 50\text{V}, R_G = 25\Omega$, Starting $T_J = 25^\circ\text{C}$
- Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty Cycle $\leq 1\%$

Typical Characteristics $T_J = 25^\circ\text{C}$, unless otherwise noted

Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current




Figure 4. Capacitance




Figure 5. Gate Charge





Figure 6. Body Diode Forward Voltage



Typical Characteristics $T_J = 25^\circ\text{C}$, unless otherwise noted

Figure 7. On-Resistance vs. Temperature




Figure 8. Threshold Voltage vs. Temperature




Figure 9. Transient Thermal Impedance




Figure 10. C_{oss} stored energy




Figure 11. Safe Operating Area




Figure A: Gate Charge Test Circuit and Waveform




Figure B: Resistive Switching Test Circuit and Waveform






Figure C: Unclamped Inductive Switching Test Circuit and Waveform



TO-247



SYMBOL	mm		
	MIN	NOM	MAX
A	4.80	5.00	5.20
A1	2.21	2.41	2.59
A2	1.85	2.00	2.15
b	1.11	1.21	1.36
b2	1.91	2.01	2.21
b4	2.91	3.01	3.21
c	0.51	0.61	0.75
D	20.80	21.00	21.30
D1	16.25	16.55	16.85
E	15.50	15.80	16.10
E1	13.00	13.30	13.60
E2	4.80	5.00	5.20
E3	2.30	2.50	2.70
e	5.44BSC		
L	19.82	19.92	20.22
L1	-	-	4.30
ΦP	3.40	3.60	3.80
ΦP1	-	-	7.30
S	6.15BSC		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for MOSFET category:

Click to view products by WPMtek manufacturer:

Other Similar products are found below :

[IRFD120](#) [JANTX2N5237](#) [BUK455-60A/B](#) [MIC4420CM-TR](#) [VN1206L](#) [NDP4060](#) [SI4482DY](#) [IPS70R2K0CEAKMA1](#) [SQD23N06-31L-GE3](#)
[TK16J60W,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#) [DMN1053UCP4-7](#) [SQJ469EP-T1-GE3](#) [NTE2384](#) [DMC2700UDMQ-7](#)
[DMN2080UCB4-7](#) [DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [DMP22D4UFO-7B](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)
[STF5N65M6](#) [IRF40H233XTMA1](#) [STU5N65M6](#) [DMN6022SSD-13](#) [DMN13M9UCA6-7](#) [DMTH10H4M6SPS-13](#) [DMN2990UFB-7B](#)
[IPB80P04P405ATMA2](#) [2N7002W-G](#) [MCAC30N06Y-TP](#) [MCQ7328-TP](#) [NTMC083NP10M5L](#) [BXP7N65D](#) [BXP4N65F](#) [AOL1454G](#)
[WMJ80N60C4](#) [BXP2N20L](#) [BXP2N65D](#) [BXT1150N10J](#) [BXT1700P06M](#) [TSM60NB380CP ROG](#) [RQ7L055BGTCR](#) [DMNH15H110SK3-13](#)
[SLF10N65ABV2](#) [BSO203SP](#) [BSO211P](#) [IPA60R230P6](#)