



Capacitor value 1000 pF

**Technical Characteristics**

**Materials:**

Insulator: Thermoplastic UL94 V-0 black  
 Contact: Copper alloy  
 Contact finish: 0,2u Au over nickel  
 Shell: steel tin plated

**Characteristics:**

Working voltage: 100 V  
 Current rating: 5A  
 Contact resistance: max. 10 MOHM  
 Insulation resistance: > 1 GOHM  
 Temperature range: -55° - 125°C

General tolerances				
tolerances	± 0,1	± 0,2	± 0,2	± 0,3
size (mm)	> 0,5 up to 3	> 3 up to 6	> 6 up to 30	> 30 up to 120

				Date	Name	DESCRIPTION				
				Drawn	11-11-02	Jelisarow	DSubFilter			
				Checked			D-Sub Filter Adapter			
						Scale	1:1	Position		SIZE
				Würth Elektronik eiSos GmbH & Co KG D-74638 Waldenburg Max-Eyth-Straße 1		Drawing.- No. 234016003				A4
REV	FILE	DATE	BY	EDV NO	234016003.dft		System :Solid Edge V20			

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Circular MIL Spec Connector](#) category:*

*Click to view products by [Sunbank](#) manufacturer:*

Other Similar products are found below :

[89075GULPR](#) [0025-262-542](#) [0025-264-3014](#) [58-570121-04S](#) [0134-213-1208](#) [0134-213-2209](#) [0025-258-000](#) [60-042022-07P](#) [60-042022-19P](#)  
[60-042022-23P](#) [60-042217-10P](#) [0114-201-1278](#) [012-0467-000](#) [602GB06EG24-61SN](#) [0134-201-1207](#) [0134-213-1006](#) [6104-207-2302](#) [6104-](#)  
[208-1902](#) [61-168211-04P](#) [61-168617-10P](#) [6131-202-19149P](#) [6131-204-21149P](#) [6131-208-13149P](#) [6131-209-17149P](#) [6131-210-11149P](#) [6131-](#)  
[211-19149P](#) [6131-216-19149P](#) [6131-259-21149P](#) [6131-259-23149P](#) [6131-265-17149P](#) [6131-265-19149P](#) [CS3100A18-1P-472](#) [CS3100A-36-](#)  
[77P](#) [CS3101A-16-55P](#) [CS3102A-10SL-55P](#) [CS3102A-14S-58P](#) [CS3102A-32-17P](#) [CS3102A32-25S](#) [CS3102C18-4P-472](#)  
[CS3106A10SL3S004](#) [CS3106A-18-73S](#) [CS3108A-14S-52S](#) [CS3108A-28-51S](#) [6162-233-1277](#) [6162-324-1231](#) [M243082296Z](#)  
[M2884010AC1S1](#) [CT0-24-10SC](#) [CT0M20-7PCAU](#) [M28840/17AC1G3](#)