	1		2		3		4	5		Γ
		.00±0.15 .00±0.15	70±0.25 6.90±0. 	- IJ./ULU.JU	PCB LAYOUT - COI PCB LAYOUT - COI RECOMMENDED PCB	А-Ф0.92 2-Ф2.30 МРОЛЕНТ VIEW	TECHNICAL CHARACTER	LISTICS JL94-V0 ASS D OVER Ni S ATING CYCLES JRE: -40°C UP TO +85°C E & ROHS VAC MAX E: 500 VAC/MIN E: > 1000 MΩ 30 mΩ MAX N MAX		E
			→ 7.12±0.25				SOLDERING JEDEC LEAD FREE WAVE PACKAGING TRAY			
ļ										0
R	HS Compliant			PROJECTION:	GENERAL TOLERANCE					
F E D					.X = <sup>+</sup> / <sub>-</sub> 0.2 .XX = <sup>+</sup> / <sub>-</sub> 0.15	WÜRTH ELEKT				$\left  \right $
) C	20-JUN-17	OTHER PINS	AK	APPROVAL: NPr	UNIT: MM		ISB 2.0 TYPE A HORIZONTA	L THT	SIZE	╢
	23-JAN-17	CERTIFIED	AK		SCALE:				<b>A4</b>	11
B A	19-JUN-15	PDF	AK		SHEET: 1/3	WERI PART NO: (	04 4 00 4 400 00 f			

1	2	3	4	5		
						Α
		322	183			в
RoHS Compliant			CARTON	60 pcs/tray 44 trays/carton 2640 pcs/carton		С
G F	PROJECTION:	GENERAL TOLERANCE .X = +/_ 0.2				
E D		.XX = <sup>+</sup> /_ 0.15				Π
С	APPROVAL: NPr	UNIT: MM	DESCRIPTION: USB 2.0 TYPE A HORIZONTA	L THT	SIZE	D
B A		SCALE: SHEET: 2/3	WERI PART NO: 614 004 190 021		<b>A4</b>	
REV DATE FILE	BY	DRAW: AK	-		.	

1	2	3	4	5	-
					_

А

В

С

## **Cautions and Warnings:**

This electronic component is designed and developed with the intention for use

in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body,

Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

R	oHS Compliant							
G				PROJECTION:	GENERAL TOLERANCE			]
F					.X = <sup>+</sup> /_ 0.2			
E					.XX = <sup>+</sup> /_ 0.15			
D						WÜRTH ELEKTRONIK		
С				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE	חן
В				]	SCALE:			Р
A	10-SEP-14	PDF	QL	]	SHEET: 3/3	WERI PART NO: DISCLAIMER	<b>A4</b>	
REV	DATE	FILE	BY	]	DRAW: QL			

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for USB Connectors category:

Click to view products by Wurth manufacturer:

Other Similar products are found below :

65-647-8-BK-BU 950 952 E8144-B01021-L A-USB B-TOP-C MUSBA511N5 MUSBD11135 217450-1 KMBVX-TH-5S-B30 896-30-004-00-000000 KUSBVX-BS1N-W30 KUSBX-AP-KIT-SCBLK KUSBX-AS2N-W KUSBX-SMT2AP1S-W KUSBX-SMT2AP1S-W30 935 957 30-498-6 SK-60A-2 17-210051 1734082-1 30-1574 30-470 30-489 30-541 30-572-3 A-USB A-2P-C MIKROE-1451 USBFTV2PEM2G USBFTVC6ZN KUSBX-AS2N-W30 KUSBX-SLAS1N-W KUSBX-SMT-AS1N-W30 4689-1 1-1734084-2 E8110-001-01 33UBARS1-04SW11 33UBAR-04SW11 USBF21ZNSCC USBBFTV6ZC 10135326-001LF M9177/3-1 USB-A-S-F-B-VT 925 4198 690-024-633-031 KUSBEX-BSFS1N-W USBFTVC6MRG UA-20BMFA-SL8001 17-250101