

## **Article Properties:**

| Properties           |   | Value | Unit | Tol. |                 |
|----------------------|---|-------|------|------|-----------------|
| Nominal Cable Length | L | 152.4 | mm   | ±2mm | RoHS<br>COMPLIA |



REACH

| Würth Elektronik eiSos GmbH & Co. KG<br>EMC & Inductive Solutions<br>Marx-Eyth-St. 1<br>74638 Waldenburg<br>Germany<br>Tell. +49 (0) (7) 42 945 - 0<br>www.we-online.com<br>eiSoe@we-online.com |   |     |
|---|---|-----|
| Tel. +49 (0) 79 42 945 - 0<br>www.we-online.com   | MC & Inductive Solutions<br>Aax-Eyth-Str. 1<br>'4638 Waldenburg | S   |
|   | el. +49 (0) 79 42 945 - 0                                       | SIZ |
|   |   | FI  |

| JaC                           | REVISION<br>001.000 | DATE (YYYY-MM-DD)<br>2020-04-30 | general tolerance<br>DIN ISO 2768-1m | -      | PROJECTION<br>METHOD | $- \bigcirc ($ | €-   |
|-------------------------------|---------------------|---------------------------------|--------------------------------------|--------|----------------------|----------------|------|
| WR-CXASY SMP Straight Jack to |                     |                                 |                                      |        |                      |                |      |
| SMP Straight Jack             |                     |                                 |                                      |        | 03321 <sup>-</sup>   | 115301         |      |
| SIZE/TYPE                     |                     |                                 | BUSINESS UNIT                        | STATUS |                      |                | PAGE |
| Flexible Cable .              | .047"               |                                 | eiCan                                | Valid  |                      |                | 1/6  |

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is not authorized tor use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety reasonable expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety reasonable expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability valuation checks for safety must be performed on every electronic component which is used in electrical circuits additions or performance.

## **Material Properties Cable:**

| Properties                   | Value Un |    |  |  |  |
|------------------------------|----------|----|--|--|--|
| Cable                        | .047"    |    |  |  |  |
| Nominal Outer Cable Diameter | 1.42     | mm |  |  |  |

## Material Properties Connector 1 & Connector 2:

| Insulator Material        | PTFE                            |
|---------------------------|---------------------------------|
| Insulator Color           | White                           |
| Center Contact Material   | Beryllium Copper                |
| Center Contact Plating    | Gold, min. 0.127 µm over Nickel |
| Body Material             | Beryllium Copper                |
| Body Plating              | Gold, min. 0.127 µm over Nickel |
| Snap Ring Material        | Beryllium Copper                |
| Snap Ring Plating         | Gold, min. 0.127 µm over Nickel |
| Heat Shrink Tube Material | PE                              |
| Heat Shrink Tube Color    | Black                           |
|                           |                                 |

## **Kind Properties:**

| •                  |             |
|--------------------|-------------|
| Interface          | MIL-STD-348 |
| Cable Type         | Flexible    |
| Cable Shielding    | Braid       |
| Connector Type 1   | SMP         |
| Gender 1           | Jack        |
| Orientation Type 1 | Straight    |
| Connector Type 2   | SMP         |
| Gender 2           | Jack        |
| Orientation Type 2 | Straight    |

## **Electrical Properties:**

| -                     | _                |                        |           |         |      |
|-----------------------|------------------|------------------------|-----------|---------|------|
| Properties            |                  | Test conditions        | Value     | Unit    | Tol. |
| Impedance             | Z                | DC~18 GHz              | 50        | Ω       |      |
| Frequency Range       | f                |                        | DC~18 GHz |         |      |
| VSWR                  |                  | DC~18 GHz              | 1.5       |         | max. |
| Insertion Loss        | IL               | DC~18 GHz              | 1.93      | dB      | max. |
| Insulation Resistance | R <sub>ISO</sub> | 500 V (DC) in 120 sec. | 5000      | MΩ      | min. |
| Withstanding Voltage  |                  | 500 V (AC) in 60 sec.  | 260       | V (RMS) | min. |

## **Mechanical Properties:**

| Properties                       | Test conditions           | Value | Unit   | Tol. |
|----------------------------------|---------------------------|-------|--------|------|
| Center Contact Retention (Axial) |                           | 7     | N      | min. |
| Mating Cycle                     | Mated with Full Detent    | 100   | Cycles |      |
| Mating Cycle                     | Mated with Limited Detent | 500   | Cycles |      |
| Mating Cycle                     | Mated with Smooth Bore    | 1000  | Cycles |      |
| Force to Engage                  | Mated with Full Detent    | 68    | N      | max  |
| Force to Engage                  | Mated with Limited Detent | 45    | N      | max  |
| Force to Engage                  | Mated with Smooth Bore    | 9     | N      | max  |
| Force to Disengage               | Mated with Full Detent    | 22    | N      | min  |
| Force to Disengage               | Mated with Limited Detent | 9     | N      | min  |
| Force to Disengage               | Mated with Smooth Bore    | 2.2   | N      | min  |
| Min. Bend Radius                 | Static/ Single            | 5     | mm     |      |
| Min. Bend Radius                 | Dynamic                   | 10    | mm     |      |
| Cable Retention                  |                           | 10    | N      | min  |

## **Certification:**


| RoHS Approval  | Compliant [2011/65/EU&2015/863]     |
|----------------|-------------------------------------|
| REACh Approval | Conform or declared [(EC)1907/2006] |

## **General Information:**


| Operating Temperature | -65 up to +165 °C |
|-----------------------|-------------------|
|-----------------------|-------------------|

|                               |  | CHECKED<br>JaC              | REVISION<br>001.000           | DATE (YYYY-MM-DD)<br>2020-04-30 | GENERAL TOLERANCE<br>DIN ISO 2768-1m | F               |                    | <b>—</b>    |
|-------------------------------|--|-----------------------------|-------------------------------|---------------------------------|--------------------------------------|-----------------|--------------------|-------------|
| ROMELIANT COMPLIANT COMPLIANT |  |                             | WR-CXASY SMP Straight Jack to |                                 |                                      |                 |                    |             |
|                               | EMC & Inductive Solutions<br>Max-Eyth-Str. 1<br>74638 Waldenburg       | SMP S                       | traight .                     | Jack                            |                                      | ORDER CODE      | <b>332111530</b> 1 |             |
|                               | Tel. +49 (0) 79 42 945 - 0<br>www.we-online.com<br>eiSos@we-online.com | SIZE/TYPE<br>Flexible Cable | .047"                         |                                 | BUSINESS UNIT<br>eiCan               | status<br>Valid |                    | PAGE<br>2/6 |

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Wirth Elektronik elSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in therefore a failure of the product is restriction, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in therefore a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Wirth Elektronik elSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in the require high safety and reliability for componence.



This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is not authorized tor use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik elSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability valuation checks for safety must be performed on every electronic component which is used in electrical incurbic for severations reperformance.



This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is not authorized tor use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik elSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability valuation checks for safety must be performed on every electronic component which is used in electrical incurbic for severations reperformance.

PROJECTION METHOD

65503321115301

ORDER CODE

STATUS

Valid

 $\overline{\bigcirc}$ 

PAGE

4/6

### **Cautions and Warnings:**

# The following conditions apply to all goods within the product series of the Connectors of Würth Elektronik eiSos GmbH & Co. KG:

#### **General:**

- This mechanical component is designed and manufactured for use in general electronic equipment.
- Würth Elektronik must be asked for written approval (following the PPAP procedure) before incorporating the components into any
  equipment in fields such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control,
  ship control), transportation signal, disaster prevention, medical, public information network, etc. where higher safety and reliability are
  especially required and/or if there is the possibility of direct damage or human injury.
- Mechanical components that will be used in safety-critical or high-reliability applications, should be pre-evaluated by the customer.
- The mechanical component is designed and manufactured to be used within the datasheet specified values. If the usage and operation conditions specified in the datasheet are not met, the component may be damaged or dissolved.
- Do not drop or impact the components, the component may be damaged.
- Prevent any damage or scratches on the component, especially on the actuator.
- Direct mechanical impact to the product shall be prevented (e.g overlapping of the PCB's).
- Würth Elektronik products are qualified according to international standards, which are listed in each product reliability report. Würth
  Elektronik does not warrant any customer qualified product characteristics beyond Würth Elektroniks' specifications, for its validity and
  sustainability over time.
- The responsibility for the applicability of the customer specific products and use in a particular customer design is always within the authority of the customer. All technical specifications for standard products do also apply to customer specific products.
- The mechanical component is designed to be used along with Würth Elektronik counterparts and tools. Würth Elektronik cannot ensure
  the reliability of these components while being used with other products.

#### **Product Specific:**

Soldering:

- The solder profile must comply with the technical product specifications. All other profiles will void the warranty.
- All other soldering methods are at the customers' own risk.

#### Cleaning and Washing:

- Washing agents used during the production to clean the customer application might damage or change the characteristics of the component, body, pins and termination. Washing agents may have a negative effect on the long-term functionality of the product.
- Using a brush during the cleaning process may deform function relevant areas. Therefore, we do not recommend using a brush during the PCB cleaning process.

#### Potting and Coating:

If the product is potted in the customer application, the potting material might shrink or expand during and after hardening. Shrinking
could lead to an incomplete seal, allowing contaminants into the components. Expansion could damage the components. We
recommend a manual inspection after potting or coating to avoid these effects.

#### **Storage Conditions:**

- A storage of Würth Elektronik products for longer than 12 months is not recommended. Within other effects, the terminals may suffer degradation, resulting in bad solderability. Therefore, all products shall be used within the period of 12 months based on the day of shipment.
- Do not expose the components to direct sunlight.
- The storage conditions in the original packaging are defined according to DIN EN 61760-2.
- The storage conditions stated in the original packaging apply to the storage time and not to the transportation time of the components.

#### Handling:

- Do not repeatedly operate the component with excessive force. It may damage or deform the component resulting in malfunction.
- In the case a product requires particular handling precautions, in addition to the general recommendations mentioned here before, these
  will appear on the product datasheet.

These cautions and warnings comply with the state of the scientific and technical knowledge and are believed to be accurate and reliable. However, no responsibility is assumed for inaccuracies or incompleteness.

|                          |   | CHECKED<br>JaC              | REVISION<br>001.000           | DATE (YYYY-MM-DD)<br>2020-04-30 | GENERAL TOLERANCE<br>DIN ISO 2768-1 m |                              | PROJECTION<br>METHOD |   | €-          |
|--------------------------|---|-----------------------------|-------------------------------|---------------------------------|---------------------------------------|------------------------------|----------------------|---|-------------|
| ROHS COMPLIANT COMPLIANT |   |                             | WR-CXASY SMP Straight Jack to |                                 |                                       |                              | •                    |   |             |
|                          | Würth Elektronik eiSos GmbH & Co. KG<br>EMC & Inductive Solutions<br>Max-Eyth-Str. 1<br>74638 Waldenburg<br>Germanv | SMP S                       | SMP Straight Jack             |                                 |                                       | ORDER CODE<br>65503321115301 |                      |   |             |
|                          | elmann<br>Tel. +49 (0) 79 42 945 - 0<br>www.we-online.com<br>elSos@we-online.com                                    | SIZE/TYPE<br>Flexible Cable | .047"                         |                                 | BUSINESS UNIT<br>eiCan                | status<br>Valid              |                      | 1 | PAGE<br>5/6 |

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik elSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability valuation checks for safety must be partient or every electronic component which is used in electrical circuits that require high safety and reliability valuation checks for safety must be partient or every electrical circuits that require high safety and reliability to estimate.

### **Important Notes**

# The following conditions apply to all goods within the product range of Würth Elektronik eiSos GmbH & Co. KG:

#### 1. General Customer Responsibility

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

#### 2. Customer Responsibility related to Specific, in particular Safety-Relevant Applications

It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications. In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component. Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at www.we-online.com.

#### 3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty.

#### 4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve specific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter.

#### 5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further queries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected.

#### 6. Product Life Cycle

Due to technical progress and economical evaluation we also reserve the right to discontinue production and delivery of products. As a standard reporting procedure of the Product Termination Notification (PTN) according to the JEDEC-Standard we will inform at an early stage about inevitable product discontinuance. According to this we cannot guarantee that all products within our product range will always be available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the current product availability expectancy before or when the product for application design-in disposal is considered. The approach named above does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.

#### 7. Property Rights

All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, development contracts as well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will remain with Würth Elektronik eiSos GmbH & Co. KG does not warrant or represent that any license, either expressed or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

#### 8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms and Conditions of Würth Elektronik eiSos Group", last version available at www.we-online.com.

| Reference and the second secon |   | CHECKED<br>JaC                | REVISION<br>001.000 | DATE (YYYY-MM-DD)<br>2020-04-30 | GENERAL TOLERANCE<br>DIN ISO 2768-1 m | _               | PROJECTION<br>METHOD |             |
|--|---|-------------------------------|---------------------|---------------------------------|---------------------------------------|-----------------|----------------------|-------------|
|  |   | WR-CXASY SMP Straight Jack to |                     |                                 |                                       |                 |                      |             |
|  | Würth Elektronik elöss GmbH & Co. KG<br>EMC & Inductive Solutions<br>Max-Eyth-Str. 1<br>74638 Waldenburg<br>Germany<br>Tel. +49 (0) 79 42 945 - 0<br>www.we-online.com<br>elSos@we-online.com | SMP Straight Jack             |                     |                                 |                                       | 65503321115301  |                      |             |
|  |   | SIZE/TYPE<br>Flexible Cable   | .047"               |                                 | BUSINESS UNIT<br>eiCan                | status<br>Valid |                      | PAGE<br>6/6 |

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability evaluation (automotive control, train control, ship control, train contro

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Cable Assemblies category:

Click to view products by Wurth manufacturer:

Other Similar products are found below :

 73-6352-10
 73-6353-3
 R285001001
 R288940004
 145111-05-12.00
 1661-C-24
 1801171170914KE
 24P104C24J1-012
 24P104C24P1-006

 24P104C24P1-018
 24P204C24J1-003
 172-2150-EX
 1800920920914PJ
 FCB-3030-ALT
 21117-046
 21117-050
 PCX-24-50
 24P103C24P2 

 003
 25P203C25P2-003
 R284008001
 R285001021
 R285426000
 R288940003
 4814-BB-24
 5260-72
 JT2N1-CL1-1F
 DLP-COAX1
 4814-K 

 48
 115101-09-06.00
 CCNTN2-MM-LL335-26
 73-6351-25
 73-6352-3
 73-6353-25
 1800920920610PJ
 GD0BQ0BQ024.0
 1-3636-600-5210

 TL8A-11SMA-11SMA-01500-51
 R284C0351060
 R288940009
 R284C0351028
 R288940002
 9702-1SL-1
 PT82NSMA
 73-6353-10

 R285020301W
 PCX-18-50
 Minibend-9
 Minibend-4
 BNC TO SMA Cable
 MIKROE-274