




SOLDER SUFFIX	CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE	6C
LF3	Sn100%	Yes	Yes	



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

- D.C. RESISTANCE (@20°C): 4-5(tie 3+4, 5+6), 0.02 ohms max.
1-8, 1.45 ohms max.
- DIELECTRIC RATING: 1000VDC, 1 minute tested by applying 1250VDC for 1 second between 1-5(tie 3+4).
- INDUCTANCE: 10.0uH ±10%, 10kHz, 100mVAC, 4-5(tie 3+4, 5+6), Ls.
- LEAKAGE INDUCTANCE: 0.15uH max., 100kHz, 10mAAC, 4-5(tie 1+8, 3+4, 5+6), Ls.
- TURNS RATIO: (1-8):(5-4) = 10:1, tie(3+4, 5+6), ±2%.
- Midcom p/n 32050R-LF3 is eiSos p/n: 750032050.

6C Wire insulation & RoHS status not affected by wire color.
Wire insulation color may vary depending on availability.

Unless otherwise specified: Tolerances: Angles: ±1° Fractions: ±1/64 Decimals: ±.005[.13]	DRAWING TITLE <h3>TRANSFORMER</h3>			PART NO. <h2>32050R-LF3</h2>	REV. 6D 8/16
	eiSos p/n: 750032050	SPECIFICATION SHEET 1 OF 1			
This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	SEE REVISION SHEET FOR REVISION LEVEL	PART# 32050R-LF3			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Power Transformers](#) category:

Click to view products by [Würth](#) manufacturer:

Other Similar products are found below :

[ET-030A](#) [F-102X](#) [F-120X](#) [F-14X-1](#) [F-181U](#) [F-18A](#) [F-199U](#) [F-19X](#) [F-202U](#) [F-204U](#) [F-206U](#) [F-227X](#) [F-238U](#) [F-239U-1](#) [F-23U](#) [F24-250-B](#)
[F-242U](#) [F-245U](#) [F-264U](#) [F-265U](#) [F-267U](#) [F-281U](#) [F-283U](#) [F-290X](#) [F-295Z](#) [F-296Z](#) [F-298Z](#) [F-3143P](#) [F-3298Z](#) [F-33U](#) [F-346X](#) [F-35U](#) [F-](#)
[364U](#) [F-392A](#) [F-395X](#) [F-397U](#) [F-412X](#) [F-47U](#) [F-55X-1](#) [F-60U](#) [F-68U](#) [F-71U](#) [F-72Z](#) [F-74U](#) [F-83A](#) [F-84AC](#) [F-85U](#) [F-86U](#) [F-9U](#) [PCT-02](#)