



CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes

more than you expect



Application of the transformer requires terminals 4&5 and 3&2 be internally connected on the PCB.

Application of the transformer allows for the leadwires between terminals 2&3 and 4&5 to solder bridge. **6B**

ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE	
D.C. RESISTANCE	4-2	tie(2+3, 4+5), @20°C	0.023 ohms ±20%
D.C. RESISTANCE	11-12	@20°C	0.034 ohms ±20%
D.C. RESISTANCE	9-10	@20°C	0.197 ohms ±10%
D.C. RESISTANCE	7-8	@20°C	0.197 ohms ±10%
INDUCTANCE	4-2	tie(2+3, 4+5), 10kHz, 100mVAC, Ls	40.0uH ±10%
SATURATION CURRENT		20% rolloff from initial	1.8A
LEAKAGE INDUCTANCE	4-2	tie(2+3, 4+5, 7+8+9+10+11+12), 100kHz, 100mVAC, Ls	0.30uH max.
DIELECTRIC	2-12	tie(8+10+12), 1875VAC, 1 second	1500VAC, 1 minute
TURNS RATIO		(7-8):(11-12)	2.86:1, ±1%
TURNS RATIO		(7-8):(9-10)	1:1, ±1%
TURNS RATIO		(7-8):(4-2), tie(2+3, 4+5)	2:1, ±1%

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Designed to comply with the following requirements as defined by IEC61558-2-16 and EN61558-2-16:

- Basic insulation for a primary circuit at a working voltage of 50Vpeak, (Operating frequency of <2MHz).

Wire insulation & RoHS status not affected by wire color.
Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications Method: Tape & Reel PKG-0868 www.we-online.com/midcom		Tolerances unless otherwise specified: Angles: ±1° Fractions: ±1/64 Decimals: ±.005 [.13] Footprint: ±.005 [.13]	DRAWING TITLE TRANSFORMER	PART NO. 750315039
6B	5/15			This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	eiSos p/n: 750315039	
6A	11/14	SEE REVISION SHEET FOR REVISION LEVEL				SPECIFICATION SHEET 1 OF 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Power Transformers](#) category:

Click to view products by [Würth](#) manufacturer:

Other Similar products are found below :

[ET-030A](#) [F-102X](#) [F-120X](#) [F-14X-1](#) [F-181U](#) [F-18A](#) [F-199U](#) [F-19X](#) [F-202U](#) [F-204U](#) [F-206U](#) [F-227X](#) [F-238U](#) [F-239U-1](#) [F-23U](#) [F24-250-B](#)
[F-242U](#) [F-245U](#) [F-264U](#) [F-265U](#) [F-267U](#) [F-281U](#) [F-283U](#) [F-290X](#) [F-295Z](#) [F-296Z](#) [F-298Z](#) [F-3143P](#) [F-3298Z](#) [F-33U](#) [F-346X](#) [F-35U](#) [F-](#)
[364U](#) [F-392A](#) [F-395X](#) [F-397U](#) [F-412X](#) [F-47U](#) [F-55X-1](#) [F-60U](#) [F-68U](#) [F-71U](#) [F-72Z](#) [F-74U](#) [F-83A](#) [F-84AC](#) [F-85U](#) [F-86U](#) [F-9U](#) [PCT-02](#)