




CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
6B D.C. RESISTANCE	1-2 @20°C	0.410 ohms ±10%
6B D.C. RESISTANCE	2-3 @20°C	0.275 ohms ±10%
6B D.C. RESISTANCE	3-4 @20°C	0.800 ohms ±10%
6B D.C. RESISTANCE	6-7 @20°C	1.08 ohms ±10%
6B D.C. RESISTANCE	5-8 @20°C	1.85 ohms ±10%
INDUCTANCE	5-8 10kHz, 100mVAC, Ls	300uH ±20%
SATURATION CURRENT	20% rolloff from initial	150mA
LEAKAGE INDUCTANCE	5-8 tie(6+7, 1+2+3+4), 100kHz, 100mVAC, Ls	1.0uH typ., 2.0uH max.
DIELECTRIC	1-8 tie(5+6), 3750VDC, 1 second	3000VDC, 1 minute
URNS RATIO	(5-8):(6-7)	2:1, ±1%
URNS RATIO	(5-8):(1-2)	4.57:1, ±1%
URNS RATIO	(5-8):(2-3)	3.56:1, ±1%
URNS RATIO	(5-8):(3-4)	2.46:1, ±1%

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Wire insulation & RoHS status not affected by wire color.  
Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications Method: <b>Tape &amp; Reel</b> PKG-1042 <a href="http://www.we-online.com/midcom">www.we-online.com/midcom</a>		Tolerances unless otherwise specified: Angles: ±1° Fractions: ±1/64 Decimals: ±.005 [.13] Footprint: ±.005 [.13]	DRAWING TITLE <b>TRANSFORMER</b>	PART NO. <b>750315319</b>
6B	5/20			This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	eiSos p/n: 750315319	SPECIFICATION SHEET 1 OF 1
6A	8/15	SEE REVISION SHEET FOR REVISION LEVEL				

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Power Transformers](#) category:*

*Click to view products by [Würth](#) manufacturer:*

Other Similar products are found below :

[ET-030A](#) [F-102X](#) [F-120X](#) [F-14X-1](#) [F-181U](#) [F-18A](#) [F-199U](#) [F-19X](#) [F-202U](#) [F-204U](#) [F-206U](#) [F-227X](#) [F-238U](#) [F-239U-1](#) [F-23U](#) [F24-250-B](#)  
[F-242U](#) [F-245U](#) [F-264U](#) [F-265U](#) [F-267U](#) [F-281U](#) [F-283U](#) [F-290X](#) [F-295Z](#) [F-296Z](#) [F-298Z](#) [F-3143P](#) [F-3298Z](#) [F-33U](#) [F-346X](#) [F-35U](#) [F-](#)  
[364U](#) [F-392A](#) [F-395X](#) [F-397U](#) [F-412X](#) [F-47U](#) [F-55X-1](#) [F-60U](#) [F-68U](#) [F-71U](#) [F-72Z](#) [F-74U](#) [F-83A](#) [F-84AC](#) [F-85U](#) [F-86U](#) [F-9U](#) [PCT-02](#)