




CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	1-3 @20°C	3.60 ohms max.
D.C. RESISTANCE	4-5 @20°C	0.514 ohms max.
D.C. RESISTANCE	6-7 @20°C	0.052 ohms max.
D.C. RESISTANCE	8-10 @20°C	0.072 ohms max.
INDUCTANCE	3-1 10kHz, 100mVAC, Ls	2.20mH ±10%
INDUCTANCE	4-5 10kHz, 100mVAC, Ls	32.00uH ±10%
INDUCTANCE	10-8 10kHz, 100mVAC, Ls	12.00uH ±11%
INDUCTANCE	7-6 10kHz, 100mVAC, Ls	4.00uH typ.
SATURATION CURRENT	3-1 20% rolloff from initial	470mA
LEAKAGE INDUCTANCE	3-1 tie(4+5+6+7+8+10), 100kHz, 100mVAC, Ls	32uH typ., 64uH max.
DISTRIBUTED CAPACITANCE	3-1 100mVAC, Cs	30.0pF typ., 50pF max.
DIELECTRIC	3-10 tie(1+4), 4000VAC, 2 seconds	-
TURNS RATIO	(3-1):(4-5)	8.24:1, ±1%
TURNS RATIO	(3-1):(10-8)	14:1, ±1%
TURNS RATIO	(3-1):(7-6)	23.3:1, ±1%

PART MUST INSERT FULLY TO SURFACE A IN RECOMMENDED GRID \* DIMENSION MAY BE EXCEEDED WITH SOLDER ONLY



6B

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Designed to comply with the following requirements as defined by IEC61558-2-16 and EN61558-2-16:

- Reinforced insulation for a primary circuit at a working voltage of 265Vrms, 400Vpeak (operating frequency of <2MHz).

Wire insulation & RoHS status not affected by wire color.  
Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications Method: Tray PKG-1030 www.we-online.com/midcom		Tolerances unless otherwise specified: Angles: ±1° Fractions: ±1/64 Decimals: ±.005 [ .13 ] Footprint: ±.001 [ .03 ]	DRAWING TITLE <b>TRANSFORMER</b>	PART NO. <b>750316878</b>
6B	2/19	SEE REVISION SHEET FOR REVISION LEVEL		This drawing is dual dimensioned. Dimensions in brackets are in millimeters.	eiSos p/n: 750316878	compliant RoHS
6A	10/17					SPECIFICATION SHEET 1 OF 1

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Power Transformers](#) category:*

*Click to view products by [Würth](#) manufacturer:*

Other Similar products are found below :

[ET-030A](#) [F-102X](#) [F-120X](#) [F-14X-1](#) [F-181U](#) [F-18A](#) [F-199U](#) [F-19X](#) [F-202U](#) [F-204U](#) [F-206U](#) [F-227X](#) [F-238U](#) [F-239U-1](#) [F-23U](#) [F24-250-B](#)  
[F-242U](#) [F-245U](#) [F-264U](#) [F-265U](#) [F-267U](#) [F-281U](#) [F-283U](#) [F-290X](#) [F-295Z](#) [F-296Z](#) [F-298Z](#) [F-3143P](#) [F-3298Z](#) [F-33U](#) [F-346X](#) [F-35U](#) [F-](#)  
[364U](#) [F-392A](#) [F-395X](#) [F-397U](#) [F-412X](#) [F-47U](#) [F-55X-1](#) [F-60U](#) [F-68U](#) [F-71U](#) [F-72Z](#) [F-74U](#) [F-83A](#) [F-84AC](#) [F-85U](#) [F-86U](#) [F-9U](#) [PCT-02](#)