




CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	1-3 @20°C	0.355 ohms max.
D.C. RESISTANCE	6-4 @20°C	0.87 ohms max.
INDUCTANCE	1-3 100kHz, 10mVAC, Ls	250uH min.
DIELECTRIC	1-6 6250 Vrms, 1 second	5000 Vrms, 1 minute
URNS RATIO	(6-4):(1-3)	3.9:1, ±2%



- ⑥C GENERAL SPECIFICATIONS:
OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.
- ⑥E⑥C Current Rating: 50mAAC
- ⑥D⑥C Voltage Time: 9VuS
- ⑥C Designed to comply with the following requirements as defined by IEC60601-1(ed); am1:
- Providing two means of Patient Protection up to working voltage of 250VAC.
- ⑥C 8mm min. creepage & clearance distance between PRI & SEC.
- ⑥C Designed to comply with the following requirements as defined by IEC60950-1, EN60950-1, UL60950-1/CSA60950-1 and AS/NZS60950.1:
- Reinforced insulation for a primary circuit at a working voltage of 250VAC, Overvoltage Category II, Pollution Degree 2, up to 2km above sea level.
- ⑥C Designed to comply with the following requirements as defined by IEC60664-1,
- Reinforced insulation for a primary circuit at a working voltage of 400VAC up to 2km above sea level.
- ⑥E Qualified to AEC-Q200.

Wire insulation & RoHS status not affected by wire color.
Wire insulation color may vary depending on availability.

AGENCY NUMBER	
UL CODE FILE# E205930	SN
UL CODE FILE# E358628	SN

REV.	DATE	Packaging Specifications	CONVENTION PLACEMENT
6E	6/21	Method: Tape & Reel	
6D	8/19	PKG-0948	
6C	6/19	www.we-online.com/midcom	
6B	5/18	SEE REVISION SHEET FOR REVISION LEVEL	

Tolerances unless otherwise specified:
Angles: ±1° Decimals: ±.005 [.13]
Fractions: ±1/64 Footprint: ±.005 [.13]

This drawing is dual dimensioned. Dimensions in brackets are in millimeters.

DRAWING TITLE
TRANSFORMER

eiSos p/n: 750343725

PART NO.
750343725

compliant RoHS

SPECIFICATION SHEET 1 OF 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Power Transformers](#) category:

Click to view products by [Würth](#) manufacturer:

Other Similar products are found below :

[ET-030A](#) [F-102X](#) [F-120X](#) [F-14X-1](#) [F-181U](#) [F-18A](#) [F-199U](#) [F-19X](#) [F-202U](#) [F-204U](#) [F-206U](#) [F-227X](#) [F-238U](#) [F-239U-1](#) [F-23U](#) [F24-250-B](#)
[F-242U](#) [F-245U](#) [F-264U](#) [F-265U](#) [F-267U](#) [F-281U](#) [F-283U](#) [F-290X](#) [F-295Z](#) [F-296Z](#) [F-298Z](#) [F-3143P](#) [F-3298Z](#) [F-33U](#) [F-346X](#) [F-35U](#) [F-](#)
[364U](#) [F-392A](#) [F-395X](#) [F-397U](#) [F-412X](#) [F-47U](#) [F-55X-1](#) [F-60U](#) [F-68U](#) [F-71U](#) [F-72Z](#) [F-74U](#) [F-83A](#) [F-84AC](#) [F-85U](#) [F-86U](#) [F-9U](#) [PCT-02](#)