
CUSTOMER TERMINAL RoHS LEAD(Pb)-FREE Sn96%, Ag4% Yes Yes





## ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER		TEST CONDITIONS	VALUE
D.C. RESISTANCE	3-1	@20°C	5.40 ohms max.
D.C. RESISTANCE	4-5	@20°C	1.20 ohms max.
D.C. RESISTANCE	7-9	@20°C	0.048 ohms max.
INDUCTANCE	3-1	10kHz, 100mVAC, Ls	1.80mH ±10%
SATURATION CURRENT		20% rolloff from initial	350mA
LEAKAGE INDUCTANCE	3-1	tie(4+5, 7+9), 100kHz, 100mVAC, Ls	20uH typ., 35uH max.
DIELECTRIC	3-7	tie(1+4), 4500VAC, 1 second	4500VAC, 1 minute
DIELECTRIC	3-4	1500VAC, 1 second	1500VAC, 1 minute
TURNS RATIO		(3-1):(4-5)	5.67:1, ±3%
TURNS RATIO		(3-1):(7-9)	17:1, ±3%

### GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

 $_{
m (6B)}$  Designed to comply with the following requirements as defined by IEC61558-2-16, Amendment 1:

- Reinforced insulation for a primary circuit at a working voltage of 400VDC.

 $_{\mbox{\scriptsize (B)}}$  Wire insulation & RoHS status not affected by wire color. Wire insulation color may vary depending on availability.

#### DETAILS SUBJECT TO CHANGE

F	REV.	DATE	Packaging Specifications	
			Method: Tray	
			FKG-0/30	$\overline{}$
	6B	6/15	www.we-online.com/midcom CONVENTION PLAN	CEMENT
	6A	2/10	SEE REVISION SHEET FOR REVISION L	EVEL

Tolerances unless otherwise specified: Angles: ±1° Decimals: ±.005 [.13] Footprint: ±.001 [.03] Fractions: ±1/64

This drawing is dual dimensioned. Dimensions in brackets are in millimeters.

DRAWING TITLE

# **TRANSFORMER**

PART NO.

750871013

SPECIFICATION SHEET 1 OF 1

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Power Transformers category:

Click to view products by Wurth manufacturer:

Other Similar products are found below:

ET-030A F-102X F-120X F-14X-1 F-181U F-18A F-199U F-19X F-202U F-204U F-206U F-227X F-238U F-239U-1 F-23U F24-250-B
F-242U F-245U F-264U F-265U F-267U F-281U F-283U F-290X F-295Z F-296Z F-298Z F-3143P F-3298Z F-33U F-346X F-35U F364U F-392A F-395X F-397U F-412X F-47U F-55X-1 F-60U F-68U F-71U F-72Z F-74U F-83A F-84AC F-85U F-86U F-9U PCT-02