

环保物料

TEL:0769-82001899

NOTES:

Voltage Rating:250V AC/DC

Current Rating:3.0 AMP,AC/DC

Dielectric Withstand Voltage:500V,AC/Minute

Contact Voltage:20 mΩ Max





Insulation Voltage:1000 mΩ Min

Operation Temperature:-40°C to +105°C

Insulator Material:Polyester,UL94 V-0

Contact Material:Brass

Contact Plating: Au or Sn Plated on Nickel Overall



Dimension antitheses list		
item	W	L
Standard	9.50	----
Alternate	----	----

				TOLERANCE UNLESS OTHERWISE		DRAWN	CK tan	XFCN兴飞连接器有限公司		SHEET	1/1		
				X.	±0.30	X°	±5°	CHKD	CONNECTORS XFCN CONNECTORS CO., LTD.		DATE	2010. 4. 12	
				.X	±0.20	.X°	±2°	APPD	PRODUCT NAME	2.54mm Box Header Connectors		UNITS	mm
				.XX	±0.08	.XX°	±1°	VIEW	PART. NO.	BH254VS-XX	SCALE	1:1	
				.XXX	±0.03	.XXX°	±0.5°				DWG NO.	009	
AO	MODIFICATION		DRAW	DATE									

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XFCN](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)