




**SPECIFICATIONS**

- 1.Voltage rating: 50V AC, DC
  - 2.Current rating: 1A, AC, DC
  - 3.Withstanding Voltage: 500V AC/minute
  - 4.Insulation resistance:100M min
  - 5.Temperature range: -25 ° C--+85 ° C
  - 6.Contact resistance: 20m max
- WAFER

Housing Material: PA9T UL 94V0  
 Pin Material: Phosphor Bronze or Brass  
 Contact Area Plating: Plated Tin or Plated Gold  
 Mates with :P1010 series Housing  
 Poles:02-20P  
 Part No.: M1010VS-2xXX-9T-R

R=卷装 无=管装  
 Pin位数



Recommand PCB Layout  
 General Tolerance±0.05

Poles	Dimensions(mm)	
	A	B
10	4.00	7.30
12	5.00	8.30
16	7.00	10.30
20	9.00	12.30
30	14.00	17.30
40	19.00	22.30
50	24.00	27.30

WWW.XFCN.COM

				TOLERANCE UNLESS OTHERWISE		DRAWN	CK tan	XFCN兴飞连接器有限公司 CONNECTORS XFCN CONNECTORS CO., LTD.		SHEET	1/1	
				X.	±0.30	X°	±5°			CHKD	DATE	2010.4.12
				.X	±0.20	.X°	±2°	APPD	PRODUCT NAME	1.00mm Crimp Style Connectors		
				.XX	±0.08	.XX°	±1°	VIEW	PART. NO.	M1010VS-2xXX-9T	UNITS	mm
				.XXX	±0.03	.XXX°	±0.5°				SCALE	1:1
A0 VER	MODIFICATION		DRAW	DATE								

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [XFCN](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)  
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#)  
[65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)  
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#) [80.063.4001.1](#)  
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-](#)  
[001000](#)