



PCB LAYOUT

SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 125V AC, DC
- 3、Temperature Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- 4、Contact Resistance: $20\text{m}\Omega$ Max
- 5、Insulation Resistance: $100\text{M}\Omega$ Min
- 6、Withstanding Voltage: 500V AC/minute
- 7、Material: Wafer Nylon46, UL94V-0
PIN Brass Tin-plated

编号

尺寸 (mm)

	A	B	
02	1.25	4.25	5.50
03	2.50	6.75	5.50
04	3.75	9.25	6.75
05	5.00	8.00	7.50
06	6.25	9.25	10.50
07	7.50	11.75	10.50
08	8.75	11.75	11.75
09	10.00	13.00	13.00
10	11.25	14.25	14.25
11	12.50	15.50	15.50
12	13.75	16.75	16.75
20	23.75	26.75	26.75

XFCN 兴飞连接器有限公司
CONNECTORS XFCN CONNECTORS CO., LTD.

CK tan

TOLERANCE UNLESS OTHERWISE

DRAWN

CHKD

APPD

VIEW

PRODUCT NAME

UNITS

SCALE

DWG NO.

MODIFICATION

DATE

VER

A0

VER

.XXX ±0.03 .XXX° ±0.5°

.XX ±0.08 .XX° ±1°

.X ±0.20 .X° ±2°

X ±0.30 X° ±5°

009

1:1

mm

2010.4.12

1/1

1.25mm Crimp Style Connectors

M1250V-14-46

PART. NO.

VIEW

6

5

4

3

2

1

10

9

8

7

6

5

4

3

2

1

G

G

F

F

E

E

D

D

C

C

B

B

A

A

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XFCN](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)