





TEL:0769-82001899

环保物料

- SPECIFICATIONS
- 1、Current Rating: 1A AC, DC
  - 2、Voltage Rating: 125V AC, DC
  - 3、Temperature Range: -25°C ~ +85°C
  - 4、Contact Resistance: 20mΩ Max
  - 5、Insulation Resistance: 100MΩ Min
  - 6、Withstanding Voltage: 500V AC/minute
  - 7、Material: Wafer Nylon46, UL94V-0  
PIN Brass Tin-plated



PCB LAYOUT

尺寸 (mm)		编号
A	B	
02	1.25	4.25
03	2.50	5.50
04	3.75	6.75
05	5.00	8.00
06	6.25	9.25
07	7.50	10.50
08	8.75	11.75
09	10.00	13.00
10	11.25	14.25
11	12.50	15.50
12	13.75	16.75
20	23.75	26.75

VER A0	MODIFICATION			DATE	XXX ±0.03	.XXX° ±0.5°	VIEW	Φ	PART. NO.	M1250V-14-46	DWG NO.	009
					.XX ±0.08	.XX° ±1°	APPD		PRODUCT NAME	1.25mm Crimp Style Connectors	SCALE	1:1
					.X ±0.20	.X° ±2°	CHKD		CONNECTORS XFCN CONNECTORS CO., LTD.	XFCN 兴飞连接器有限公司	UNITS	mm
					X. ±0.30	X° ±5°	DRAWN	CK tan	CONNECTIONS XFCN CONNECTORS CO., LTD.	兴飞连接器有限公司	DATE	2010.4.12
					TOLERANCE UNLESS OTHERWISE							

10 9 8 7 6 5 4 3 2 1

A B C D E F G

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [XFCN](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)