


Front Bend

SPECIFICATIONS:

- Current rating:4A AC,DC
- Voltage rating:250V AC,DC
- Temperature range:-40°C~+130°C
- Contact resistance:3.0mVMax.
- Insulation resistance:5000MVMIn.
- Withstanding Voltage:2200V AC/minute
- UL File No:E304945
- Contact:0.64mm squareX18.00mm Length
- Material:HSG:Nylon66 UL94V-0
TER:Brass, Tin plated
- HSG and PIN solid needle bearing:2.0kg(min)
- Solder Resistance:Dip connector terminal tails in solder :Solder duration:4±0.5 Seconds; Solder temperature:245°C±0.5°C
- Part NO:M2545R-N-K (A)



Part NO	A	B	Part NO	A	B
2	5.08	2.54	10	25.40	22.86
3	7.62	5.08	11	27.94	25.40
4	10.16	7.62	12	30.48	27.94
5	12.70	10.16	13	33.02	30.48
6	15.24	12.70	14	35.56	33.02
7	17.78	15.24	15	38.10	35.56
8	20.32	17.78	16	40.64	38.10
9	22.86	20.32			

Part name (零件名称)	Edition (版本)	Date (日期)	THIRD ANGLE PROJECTION	UNIT:mm	Tolerance: .000 ±0.10 .00 ±0.20 .0 ±0.30
M2545R-N-K(A)	B	2010.05.13			
drawing number (图号)			CRS012-02		

东莞市兴飞连接器有限公司

Drawing
(制图) 吕叔锋

Confirmation
(审核)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XFCN](#) manufacturer:

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)