



P. C. B LAYOUT

Technical Data

Material:  
 Pin(outer sleeve):Brass,machined CuZn38Pb2  
 Plating(outer sleeve):  
 Tin Plated:2µm/80µm"NI, 5µm/200µ"Sn  
 Gold Plated:2µm"/80µm"Ni, 0.8µ" gold  
 Plating(Contact ):2µm/80µ"NI, gold or Tin plated  
 Insulator:PPS UL94V-0  
 Clip(Contact 4 Flinger):Beryllium copper, heat teated  
 Mating pin□:0.40mm/0.66mm

Electrical:

Current rating:3Amps/contact max.  
 Contact resistance:≤4mΩ/contact  
 Insulation resistance:≥1000MΩ at V=100V  
 Dielectric Withstanding Voltage:1000V AV Min  
 Operating voltage:60VAC/DC

Mechanical:

-Insertion:0.7N typ  
 -Withdrawal:0.4N typ  
 Mechanical life:min 500 cycle  
 Operating temperature:-40° C to+105° C  
 Soldering temperature:+255° C

				TOLERANCE UNLESS OTHERWISE		DRAWN	CK tan	<b>XFCN</b> 兴飞连接器有限公司 XFCN CONNECTORS CO.,LTD.	SHEET	1/1			
				X.	±0.30	X°	±5°		CHKD	DATE	2020.04.12		
				.X	±0.20	.X°	±2°		APPD	UNITS	mm		
				.XX	±0.08	.XX°	±1°		VIEW	SCALE	1:1		
AO	MODIFICATION			DRAW	DATE	.XXX	±0.03	.XXX°	±0.5°	PRODUCT NAME	2.00mm Machined Female Header	DWG NO.	009
VER									PART. NO.	MF200V-12-xx-0740			

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [XFCN](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)  
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#)  
[66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)  
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#)  
[80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-001000](#)  
[803-43-024-10-001000](#)