



- 1、端子原材料(Terminal raw materials):H62镀镍(H62 nickel plating)。
- 2、端子原材料料(Seat materials): Black Thermoplastic, UL 阻燃度94 V0。
- 3、可焊性Solderability: max. 260 °C, 10 s (Wave)
- 4、适用于装配电路板(Suitable for circuit board assembly)。
- 5、装配方式(Assembly way): 插入、焊接(insert, welding)。
- 6、通过认证Agency Approvals:

For Fusc	Rated Ampcragc	Rated Voltage	Operating Power	Contact Resistance	Insulation Resistance	Dielectric Strcn
适配保险丝	额定电流	额定电压	额定功率	接触电阻	绝缘电阻	耐压
5x20mm	10A	250V	1.6W	>5MΩ	>100MΩ	>300Vac/60"

TOLERANCE UNLESS OTHERWISE		DRAWN	CK tan	XFCN兴飞连接器有限公司 CONNECTORS XFCN CONNECTORS CO., LTD.			DATE	DATE	DATE	DATE	DATE	DATE
X. ±0.30	X°. ±5°			PRODUCT NAME	PART. NO.	PTF-77	DWG NO.	009	1/1	2010.4.12	UNITS	mm
.X. ±0.20	.X°. ±2°	APPD		5X20mm 保险丝座			SCALE	1:1				
.XX ±0.08	.XX°. ±1°											
.XXX ±0.03	.XXX°. ±0.5°	VIEW										
MODIFICATION												
VER A0												

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Fuse Holders](#) category:*

*Click to view products by [XFCN](#) manufacturer:*

Other Similar products are found below :

[ANS-H](#) [PTF-15](#) [PTF-77](#) [XF-003](#) [XF-007](#) [XF-008](#) [XF-101](#) [XF-505P](#)