




环保物料

TEL:0769-82001899

SPECIFICATIONS

- 1. Current Rate :1AMP
- 2. Operation Temperature:-40° C to+105° C
- 3. Contact Resistance :20m Ω Max.
- 4. Insulation Resistance:1000M Ω Min.
- 5. WithstandING Voltage :AC 500V
- 6. Insulator Material :Polyester(UL94V-0)
Standard:Nylon-PA6T
- 7. Contact Material :Brass
- 8. Contact plating :Au or Sn over 50U" Ni



PCB LAYOUT

				TOLERANCE UNLESS OTHERWISE		DRAWN		CK tan	XFCN 兴飞连接器有限公司 XFCN CONNECTORS CO.,LTD.		SHEET	1/1		
				X.	±0.30	X°	±5°	CHKD			DATE	2020.04.12		
				.X	±0.20	.X°	±2°	APPD			PRODUCT NAME	1.27mm Pin Header Connectors	UNITS	mm
				.XX	±0.08	.XX°	±1°	VIEW			PART. NO.	PZ127V-21-xx-1000	SCALE	1:1
AO	MODIFICATION			DRAW	DATE	.XXX	±0.03	.XXX°	±0.5°		DWG. NO.	009		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [XFCN](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#) [622-0430](#) [622-3653LF](#)
[63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-047](#) [65817-010LF](#)
[65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#)
[70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-T012/H](#) [80.063.4001.1](#)
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-](#)
[001000](#)