





Recommended P.C.B Layout  
P.C.B Board Tolerance±0.05

NOTES:

Voltage Rating:250V AC/DC  
Current Rating:3.0A AC/DC  
Dielectric Withstand Voltage:500V AC/minute  
Contact Voltage:20M Max.  
Insulation Voltage:1000M Min  
Operation temperature:-40 °C to +105 °C  
Insulator Material:Polyester.Ul94V-0  
Contact Material:Brass  
Contact Plating:AuorSn Plated on Nickel Overall



塑胶高度可选 (mm)				常用
H	1.0	1.5	2.0	2.54

Dimension antitheses list				
item	PA	---	PC	L
Standard	6.00	---	3.00	11.50
Alternate	---	---	---	---

				TOLERANCE UNLESS OTHERWISE		DRAWN CK tan		XFCN兴飞连接器有限公司		SHEET 1/1	
				X. ±0.30 X° ±5°		CHKD		CONNECTORS XFCN CONNECTORS CO., LTD.		DATE 2010. 4. 12	
				.X ±0.20 .X° ±2°		APPD		PRODUCT NAME 2.54mm Pin Header Connectors		UNITS mm	
				.XX ±0.08 .XX° ±1°		VIEW		PART. NO. PZ254V-12-XX		SCALE 1:1	
AO				.XXX ±0.03 .XXX° ±0.5°		Φ				DWG. NO. 009	
VER		MODIFICATION		DRAW		DATE					

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [XFCN](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [891-007-9SS-BST1T](#) [000-34000](#) [0008550134](#) [0009482033](#) [0009507031](#) [57102-F02-18ULF](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [CSU011177004](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [644827-2](#) [647662-1](#) [65039-019ELF](#) [65692-001LF](#) [65781-018](#) [65781-047](#)