








Transformers



Dimensions (In.)

■ DIMENSIONS AND PERMISSIBLE RIPPLE CURRENT

- Type: shielded audio
- Core size: EI-14
- Impedance: $\pm 10\%$ @ 1KHz
- D.C. resistance: $\pm 15\%$
- Breakdown voltage: 100VAC hipot for 1 minute
- Insulation: $>10M\Omega$ @ 100VDC
- Maximum output: 75mW
- Soldering temperature: 230°C~270°C
- Frequency response: $\pm 2dB$, 300Hz~3.5KHz
- RoHS Compliant

Mouser Stock No.	Impedance Ω		Resistance Ω	
	Pri.	Sec.	Pri.	Sec.
429-7201-RC	500	8	35	1
429-7202-RC	10K	2K	580	200
429-7209-RC	500	500	40	38
429-7216-RC	600	600	65	55
429-7218-RC	7K	10K	400	385



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Audio Transformers](#) / [Signal Transformers](#) category:

Click to view products by [Xicon](#) manufacturer:

Other Similar products are found below :

[CX2041NLT](#) [MGPWT-00449-P](#) [PE-64961](#) [H1302FNLT](#) [H5008FNL](#) [H5012FNL](#) [H5020FNLT](#) [H5077NLT](#) [H5079NLT](#) [H5084FNLT](#)
[B78476A9558A003](#) [1812WBT2-4](#) [1879479-1](#) [HX2260FNL](#) [HX5014FNL](#) [EX2024FNL](#) [FL1066](#) [T1137NLT](#) [T3012NL](#) [PE-65812FNL](#) [PE-65848FNLT](#) [H1174FNL](#) [H1302FNL](#) [H5015FNL](#) [H5019EFNL](#) [H5062FNLT](#) [CX2047LNL](#) [MGPWT-00059-P](#) [MGPWT-00266-P](#) [MGPWT-00278-P](#) [MGPWT-00431-P](#) [TTC-100](#) [TTC-143-H](#) [TTC-5032-1](#) [BX1194WNLT](#) [HX1234NLT](#) [HX5008FNLT](#) [HX5019FNL](#) [HX5084NL](#) [3-1879385-5](#) [TX1263NLT](#) [4-1879391-0](#) [T1142NL](#) [HX6101FNL](#) [HX5084FNL](#) [HX1148NL](#) [HX5020FNLT](#) [HX5014FNLT](#) [T1124NL](#)
[1879732-1](#)