



- SPECIFICATIONS:**
- ELECTRICAL CHARACTERISTICS:**
 - RATING: 12V, 4A Min.
 - CONTACT RESISTANCE: 50 MILLIOHMS Max. FOR INITIAL, 80 MILLIOHMS Max. AFTER 5000 CYCLES
 - INSULATION RESISTANCE: 100 MEGAOHMS Min BY 500V DE AFTER 1 MINUTE.
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V RMS AFTER 1 MINUTE
 - MECHANICAL CHARACTERISTICS:**
 - INSERTION FORCE: 0.3~3.0 KGF (2.94~29.4N)
 - WITHDRAWAL FORCE: 0.3~3.0 KGF (2.94~29.4N)
 - LIFE TEST: 5,000 CYCLES MIN.

NO.	PART NAME	QTY	MATERIAL (THICK)	PLATING (COLOR)
1	HOUSING	1	PA9T	Black
2	TERMINAL 4#	1	C2680R-EH T=0.30	Ag10U*,NiE50U*
3	TERMINAL 3#	1	C2680R-EH T=0.30	Ag10U*,NiE50U*
4	TERMINAL 2#	1	C5210R-EH T=0.30	Ag10U*,NiE50U*
5	TERMINAL 1#	1	C2680R-EH T=0.30	Ag10U*,NiE50U*

广东星坤科技股份有限公司

生 日期

文件 工程 章

REVISIONS

UNSPECIFIED TOLERANCES

www.xk-ug.cn www.helloxkb.com www.helloxkb.cn

DSND	DATE	SCALE: N/A	MODEL TYPE: DC POWER JACK
DWN	DATE	VIEW:	PART NO.:
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	DC-105-4A-1.6
KKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DC Power Connectors](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[B04P-VL-VN-1.8](#) [1600206-1](#) [163-0308-EX](#) [163-4012-EX](#) [163-4117-EX](#) [163-7421](#) [163-MJ22-EX](#) [171-0721-EX](#) [KLDX-SMT-0202-BPTR](#)
[163-0179-EX](#) [163-1000-EX](#) [163-4007-EX](#) [163-4015-EX](#) [171-0722-E](#) [171-7391](#) [K596](#) [KLD-0201-BC](#) [KPPX-D](#) [4C6831AX](#) [TS3PNJ](#)
[E16550-0008](#) [VLP-08V-1](#) [DC PLUG-P1M-P1MR](#) [XT90IPW22-M](#) [09758](#) [09442](#) [AS120-M](#) [09759](#) [09760](#) [CP30240](#) [TAMIYA-M](#) [TAMIYA-](#)
[MT1](#) [TAMIYA-MT2](#) [4840.1200](#) [4840.2202](#) [C5080HI-04P-18 + C5080HI-C](#) [JC-138](#) [JC-210](#) [JPO-25 \(FC6814\)](#) [JYO-26 \(FC6811\)](#) [JYO-29](#)
[\(FC68102\)](#) [KLB 3](#) [KLBM 3](#) [KLBPS 3](#) [KLS 10 SCHWARZ](#) [KLS 40 SCHWARZ](#) [KPJXHT-4S](#) [DC-10A FC68148](#) [DC-10B \(FC68149\)](#)
[WKLS 2](#) [WKLS 40](#)