



- Technology Request:
- 1.Outlook:No burr, no hurt.
  - 2.Electronic performance:
    - a:Insulation resistance: Above DC500V/100MΩ;
    - b:Endure voltage:AC500V at 1 minute;
    - c>Contact resistance:Under 30mΩ;
  - 3.Insertion force & withdrawal force:0.3-3kgf.
  - 4.Salt spray test:24H.
  - 5.Meet RoHS.
  - 6.Remork \* is important specificotion.

	MATERIAL	PLATING
PLASTIC	PBT	Black
termina 2	Brass	NI
termina 3	Brass	NI
termina 4	Phosphor Bronze	NI

					DSND		DATE		SCALE: N/A	DC POWER JACK			
ΔX					ANGLAR	±5°	DWN		VIEW:	PART NO.:			
ΔX					X.X	±0.2mm	CHKD		UNIT: mm/in	DWG NO.:			
ΔX					X.XX	±0.1mm	APPD		SIZE: A4	DC-351D-5A-1.35			
MARK	DESCRIPTION	DATE	REVISED	APPROVED	X.XXX	±0.05mm				WEIGHT	SHEET	REVISION	
REVISIONS					UNSPECIFIED TOLERANCES			XKB INDUSTRIAL PRECISION CO.,LIMITED			1.0g	1/1	A0
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn													

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [DC Power Connectors](#) category:*

*Click to view products by [XKB](#) manufacturer:*

Other Similar products are found below :

[B04P-VL-VN-1.8](#) [1600206-1](#) [163-0308-EX](#) [163-4012-EX](#) [163-4117-EX](#) [163-7421](#) [163-MJ22-EX](#) [171-0721-EX](#) [KLDX-SMT-0202-BPTR](#)  
[163-0179-EX](#) [163-1000-EX](#) [163-4007-EX](#) [163-4015-EX](#) [171-0722-E](#) [171-7391](#) [K596](#) [KLD-0201-BC](#) [KPPX-D](#) [4C6831AX](#) [TS3PNJ](#)  
[E16550-0008](#) [VLP-08V-1](#) [DC PLUG-P1M-P1MR](#) [XT90IPW22-M](#) [09758](#) [09441](#) [AS120-F](#) [09442](#) [AS120-M](#) [09759](#) [09760](#) [CP30240](#)  
[TAMIYA-M](#) [TAMIYA-MT1](#) [TAMIYA-MT2](#) [4840.1200](#) [4840.2202](#) [C5080HI-04P-18 + C5080HI-C](#) [JC-138](#) [JC-210](#) [JPO-25 \(FC6814\)](#) [JYO-](#)  
[26 \(FC6811\)](#) [JYO-29 \(FC68102\)](#) [KLB 3](#) [KLBM 3](#) [KLBPS 3](#) [KLS 10 SCHWARZ](#) [KLS 40 SCHWARZ](#) [KPJXHT-4S](#) [DC-10A FC68148](#) [DC-](#)  
[10B \(FC68149\)](#) [WKLS 2](#)