



| PART NO. | NO.OF POS. | DIM.A | DIM.B | Cover/Red (R) | | Cover/Blue (BL) | |
|----------|------------|-------|-------|----------------|-----------|-----------------|-----------|
| | | | | Projection (P) | Short (S) | Projection (P) | Short (S) |
| DS-01 | 1 | 4.06 | | DS-01RP | DS-01RS | DS-01BLP | DS-01BLS |
| DS-02 | 2 | 6.6 | 2.54 | DS-02RP | DS-02RS | DS-02BLP | DS-02BLS |
| DS-03 | 3 | 9.14 | 5.08 | DS-03RP | DS-03RS | DS-03BLP | DS-03BLS |
| DS-04 | 4 | 11.68 | 7.62 | DS-04RP | DS-04RS | DS-04BLP | DS-04BLS |
| DS-05 | 5 | 14.22 | 10.16 | DS-05RP | DS-05RS | DS-05BLP | DS-05BLS |
| DS-06 | 6 | 16.76 | 12.70 | DS-06RP | DS-06RS | DS-06BLP | DS-06BLS |
| DS-07 | 7 | 19.3 | 15.24 | DS-07RP | DS-07RS | DS-07BLP | DS-07BLS |
| DS-08 | 8 | 21.84 | 17.78 | DS-08RP | DS-08RS | DS-08BLP | DS-08BLS |
| DS-09 | 9 | 24.38 | 20.32 | DS-09RP | DS-09RS | DS-09BLP | DS-09BLS |
| DS-10 | 10 | 26.92 | 22.86 | DS-10RP | DS-10RS | DS-10BLP | DS-10BLS |
| DS-12 | 12 | 32 | 27.94 | DS-12RP | DS-12RS | DS-12BLP | DS-12BLS |

SPECIFICATION

Contact Rating: 25mA,24V DC
Contact Resistance: 50mΩ max
Insulation Resistance: 100mΩ min.500V DC
Dielectric Strength: 500V AC/1minute
Operating Force: 1,000gf max
Travel: 2mm
Operating Life: 3000cycles
Operating Temp: -20℃~+70℃
Storage Temp: -30℃~+80℃

| ITEM | PAPT NAMF | QTY | MATERIAL | FINISHING |
|------|-----------|-----|--------------|---------------------------------------|
| ④ | Terminal | | Copper Alloy | T: Tin plated G:Plating Gold ≥15MU |
| ③ | Base | 1 | Pa66 | Black |
| ② | Keystake | 1 | Pa66 | White |
| ① | Cover | 1 | Pa66 | Black Blue Red |

| DSND | DATE | SCALE: N/A | MODEL TYPE: |
|--------------------------------------|------|------------|---------------------------|
| DWN | DATE | VIEW: | DIP SWITCH |
| CHKD | DATE | UNIT: mm | PART NO.: |
| APPD | DATE | SIZE: A4 | DWG NO.: DS-XX-X-X |
| XKB INDUSTRIAL PRECISION CO.,LIMITED | | | WEIGHT: 1.0g |
| | | | SHEET: 1/1 |
| | | | REVISION: A0 |

| MARK | DESCRIPTION | DATE | REVISED | APPROVED | UNSPECIFIED TOLERANCES |
|------|-------------|------|---------|----------|------------------------|
| △X | | | | | ANGLAR ±5° |
| △X | | | | | X.X ±0.2mm |
| △X | | | | | X.XX ±0.1mm |
| | | | | | X.XXX ±0.05mm |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DIP Switches/SIP Switches](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[78M03S](#) [79B10T](#) [8136-475G4T](#) [G7G-1A2-CB-DC12](#) [A7SS-M](#) [DBP 2110](#) [DBP 2112](#) [DBS1008](#) [DHN02FTVTR](#) [DHN10T](#) [DHS108](#) [DM-08](#)
[DP-10-H](#) [DPL08TN](#) [DRD16CSE04](#) [DRR4010](#) [DRR60016](#) [DRS4016](#) [BD06E](#) [1825008-1](#) [1825444-1](#) [218-8LPSTF](#) [219-6LPSTRF](#)
[25.350.0653.0](#) [LA2-DC12](#) [SBS 5004 TG](#) [SDA10H1BDA](#) [97R06ST](#) [A2C-2A5](#) [1825444-7](#) [ADE08SA04](#) [ADE12S04](#) [2-1825058-8](#) [CCVA](#)
[2.5/ 4-G-5.08 P26THRR32](#) [25.330.0653.1](#) [25.352.0353.0](#) [MDG305ST](#) [IKN0600000](#) [IKN0800000](#) [LA2-002-DC24](#) [DBP2008](#) [DBS1003](#)
[DBS2008](#) [438872000](#) [WT11-D1-06](#) [DM-02](#) [DRD10CRAE04](#) [DRS1604](#) [DSR02T](#) [DSS 208 N](#)