



NOTE:

- 1.Rating: DC 5V 10mA
- 2.Contact Resistance:100mΩMAX
- 3.Insulation Resistance:100mΩMIN
- 4.Soldering Temper: 260±5°/5s
- 5.Mechanical Life: 100,000 cycles
- 6.Ever Portion 80±50gf
- 7.Push Portion 205±80gf
- 8.Travel:-24° 0° +24°

ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	5	Phosphor Bronze	Plating silver		
④	Base	1	Lcp			
③	Spring	1	Sus	Natural		
②	Cover	1	Sus	Natural		
①	Keystake	1	Ppa			

广东星坤科技股份有限公司

生效日期

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW:	MULTI-FUNCTIONAL SWITCH
CHKD	DATE	UNIT: mm/in	PART NO.:
APPD	DATE	SIZE: A4	DWG NO.: TM-2011A
XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT SHEET REVISION
			1.0g 1/1 A0

文件工程章

www.helloxkb.com www.helloxkb.com www.helloxkb.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multi-Directional Switches](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[RA3CSH6A](#) [APTCFVTR](#) [RKJXW2014001](#) [TSWA-3N-CUP2-LFS](#) [TSW A-3N-CUP-LFS](#) [3J2115-200N](#) [3J2015-200](#) [3J2015-200N](#) [TM-2011A](#) [10*10*9-6P WX](#) [T4-0010](#) [T4-CN211N](#) [7*7*5-6P-L WX](#) [7*7*5-6P WX](#) [7*7*6-6P-L WX](#) [7*7*6-6P WX](#) [RKJXK1210002](#) [RKJXK122000D](#) [RKJXK122400Y](#) [RKJXL100401V](#) [RKJXM1015004](#) [RKJXM2E13001](#) [RKJXM2E13004](#) [RKJXS1004001](#) [RKJXT1F42001](#) [RKJXV1220001](#) [RKJXV1224005](#) [RKJXW1014002](#) [RKJXY1000006](#) [SKQUDBE010](#) [SKRHAAE010](#) [SKRHABE010](#) [SKRHACE010](#) [SKRHADE010](#) [SLLB120100](#) [SLLB120200](#) [SLLB120300](#) [SLLB510100](#) [SLLB510200](#) [SLLB520100](#) [SLLB520200](#) [SRBE110301](#) [SRBE210200](#) [AMPTFP2VTR](#) [D16202](#) [PHAP4383V](#) [3302](#) [QS1](#) [KQS1](#) [BK S C](#) [Tsw A-3n-Cb11 Lfs](#) [TSW A-3N-C-LFS](#)