



Specifications  
 CONTACT RATING:0.1A 30 VDC  
 MECHANICAL ELECTRICAL LIFE:50,000 cycles  
 CONTACT RESISATNCE:150Ωmax. initial  
 INSULATION RESISATNCE:100Ωmin. 100VDC  
 OPERATING TEMPERATURE:-20℃to+70℃  
 DIELECTRIC STRENGTH:100 volts AC 60 HZ  
 PACKAGING:Bulk

|      |                |        |     |                 |                |        |
|------|----------------|--------|-----|-----------------|----------------|--------|
| ⑥    | Spring         |        | 1   | Sus             | Natural        |        |
| ⑤    | Contact Spring | ---    | 1   | Phosphor Bronze | Plating silver | ---    |
| ④    | Terminal       | ---    | 2   | Phosphor Bronze | Plating silver | ---    |
| ③    | Base           | ---    | 1   | Nylon           |                | ---    |
| ②    | Cover          | ---    | 1   | Nylon           |                | ---    |
| ①    | Keystake       | ---    | 1   | Nylon           |                | ---    |
| ITEM | PAPT NAMF      | TER,NO | QTY | MATERIAL        | FINISHING      | REMARK |

|                        |  |      |  |   |                                     |
|------------------------|--|------|--|---|-------------------------------------|
| DSND                   |  | DATE |  | SCALE: N/A                                  | MODEL TYPE:<br><b>DETECT SWITCH</b> |
| DWN                    |  | DATE |  | VIEW:                                       | PART NO.:                           |
| CHKD                   |  | DATE |  | UNIT: mm/in                                 | DWG NO.: <b>TM-W-09</b>             |
| APPD                   |  | DATE |  | SIZE: A4                                    |                                     |
| UNSPECIFIED TOLERANCES |  |      |  | <b>KXB INDUSTRIAL PRECISION CO.,LIMITED</b> | WEIGHT<br>1.0g                      |
|                        |  |      |  |   | SHEET<br>1/1                        |
|                        |  |      |  |   | REVISION<br>A0                      |

| ΔX  | DESCRIPTION | DATE | REVISED | APPROVED | units: mm              |
|---|-------------|------|---------|----------|------------------------|
| ΔX  |             |      |         |          | tolerance: X.X ±0.2mm  |
| ΔX  |             |      |         |          | X.XX ±0.1mm            |
| MARK  |             |      |         |          | X.XXX ±0.05mm          |
| REVISIONS                                     |             |      |         |          | UNSPECIFIED TOLERANCES |
| www.xk-dg.cn www.helloxkb.com www.helloxkb.cn |             |      |         |          |                        |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Basic / Snap Action Switches](#) category:*

*Click to view products by [XKB](#) manufacturer:*

Other Similar products are found below :

[5SM901-S12](#) [5SM9-S12N195](#) [602EN532](#) [602EN535-RB](#) [602HE5-RB1](#) [604HE162](#) [604HE223-6B](#) [624HE17-RB](#) [6HM82](#) [6HM89](#) [6SE1](#)  
[6SX1-H58](#) [70500216](#) [70599106](#) [71051](#) [MBH2731](#) [79211923](#) [79218589](#) [7AS12](#) [MIL30126AB6BBMD4A12XAU](#) [ML-1155](#) [ML-1376](#)  
[831010C3.0](#) [831090C2.EL](#) [83131904](#) [84212012](#) [8AS239](#) [8HM73-3](#) [8SX26-H33](#) [914CE1-6G](#) [PL-100](#) [11SM1077-H4](#) [11SM1077-H58](#)  
[11SM1-TN107](#) [11SM405](#) [11SM8423-H2](#) [11SX37-T](#) [11SX48-H58](#) [11SM2442-T](#) [11SM76-T](#) [11SM77-H58](#) [11SM863-T](#) [11SM866](#) [A7CN-](#)  
[1M-1-LEFT](#) [A831700C7.0](#) [121EN188-R](#) [1245.0120](#) [125EN56-RB](#) [1267.0101](#) [1267.7101](#)