

Specifications:

规格:

Current rating:3A AC/DC 额定电流: 3A AC/DC

Withstanding voltage:1000

AC/minute

耐受电压: ≥1000V AC/分钟

Temperature range:-25 °C-+105 °C

温度范围: -55℃-+105℃

Insulation resistance:500MΩMIN

绝缘电阻: ≥500MΩ

Contact resistance:25mΩMAN

接触电阻:≤25mΩ

Materiai:

材料:

Contacts:Brass

接触: 黄铜

Insulator:PBT+30 %

绝缘体: PBT+30%

Shell(Fead):SPCC

外壳:铁

MECHANIAL CHATACTERICS:


插拔力:

Contact Insertion force:300gf MAX

插入力:最大300gf

Contact Separation Force:25gf MIN

拔出力: 最小25gf



5.80 [0.227]


Autodesk



- ① Series N0.
- 2 Row No.Pin No.XX-09;15;25;37
- Welding Board Angle :F-Fmale
- 4T: Tradutional C: Car-pin
- ⑤ Planting Categotry: 1:1U 2:2U 3:3U 4:5U 5:15U 6:30U 7:Au Sn
- 6B:BLACK W:White BL:Blue Y:Yellow G:Green R:Red
- 1:TYPE-1; 2:TYPE-2; 3:TYPE-3; 4:TYPE-4; 5:TYPE-5

TYPE-2加前铆(不通孔)

TYPE-3加后铆(通孔)



NO.POS	A±0.38	B±0.13	C±0.20	D±0.38
9PIN	16.33	24.99	30.80	19.28
15PIN	24.66	33.32	39.20	27.65
25PIN	38.35	47.04	53.10	41.20
37PIN	54.80	63.50	69.40	57.44

							DSN	
					units:	mm	DWN	
ΔX					tolerance:		12	
ΔX						±0.2mm] снк	
ΔΧ					X.XX	±0.1mm	\vdash	
MARK	DESCRIPTION	DATE	REVISED	APPROVED	X.XXX	±0.05mm	APP	
	REVISIONS UNSPECIFIED TOLERANCES					TOLERANCES	Xĸ	
	www.xk-dg.cn www.helloxkb.com www.helloxkb.cn							

DSND		DATE		SCALE: N/A	MODEL TY	PE:	
DWN		DATE		VIEW:	PART NO.:		
CHKD		DATE		UNIT: mm/in	DIMO NO		
APPD		DATE		SIZE: A4	DWG NO.:	(01XXFXXX	X
VIZE INDUCTRIAL EDECICION CO. LIMITED				WEIGHT -SHEET REVIS			
XKB INDUSTRIAL PRECISION CO.,LIMITED			1.0g	1/1	A0		

Autodesk

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for HDMI, Displayport & DVI Connectors category:

Click to view products by XKB manufacturer:

Other Similar products are found below:

30-1231 30-528 30-504 30-519 33DVIR-24S1B 47648-2000 2002-400 TC142X 769-103/021-000 1932649-1 CP30200GM3 67881

HAFBF HBLBH HBLBI HAFBG HAFBH HAGBF HAGBG HAGBI HAGBJ HBLBJ AABIE AABIF AABIG AABIH AABII AABIJ

AABIK AABIL AACBE AACBF AACBG ABIBF ABIBG ABIBH 42154 AACBH AACBI AACBJ AACBK AACBL AAIBD AAIBF

AAIBH AAIBI AANBF AANBG AANBH AANBI