



Specifications:

规格:  
 Current rating:3A AC/DC  
 额定电流: 3A AC/DC  
 Voltage rating:250V AC  
 额定电压: 250V AC  
 Withstanding voltage:500V AC/MIN  
 耐受电压: ≥500V AC/分钟  
 Temperature range:-55℃-+105℃  
 温度范围: -55℃-+105℃  
 Insulation resistance:1000MΩMIN  
 绝缘电阻: ≥1000MΩ  
 Contact resistance:30mΩMAN  
 接触电阻:≤30mΩ  
 Material And FINISHED:  
 材料和成本:  
 INSULATOR:PBT UL 94V-0  
 绝缘体: PBT UL 94V-0  
 SHELL: SPCC-SD Plated Ni / Au / Sn  
 外壳: 铁合金 镀镍/金/锡  
 CONTACT MATERIAL:COPPER ALLOY  
 触点材料: 铜合金

X03 XX WT X X X  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series NO.
- ② Row No.Pin No:XX-09;15;25;37
- ③ Welding Board Angle :W-Male
- ④ T:Tradutional
- ⑤ Planting Categoty:1:1U' ;2:2U' ;3:3U' ;4:5U' ;5:15U' 6:30U' ;7:AuSn
- ⑥ B:Black W:White BL:Blue Y:Yellow G:Green R:Red
- ⑦ 1:TYPE-1; 2:TYPE-2; 3:TYPE-3; 4:TYPE-4; 6:TYPE-6

| NO.OF CONTACT | A     | B     | C     |
|---------------|-------|-------|-------|
| 09            | 30.81 | 24.99 | 16.92 |
| 15            | 39.14 | 33.32 | 25.25 |
| 25            | 53.04 | 47.04 | 38.96 |
| 37            | 69.32 | 63.50 | 55.42 |

| 柳合方式 | TYPE-1:柳合 | TYPE-6:直柳锁 | TYPE-3:叉锁 | TYPE-2:柳合锁螺丝 |
|------|-----------|------------|-----------|--------------|
| 图式   |           |            |           |              |

|                                      |  |             |                       |
|--------------------------------------|--|-------------|-----------------------|
| DSND                                 |  | SCALE: N/A  | MODEL TYPE: D-USB     |
| DWN                                  |  | VIEW:       | PART NO.: X03XXWTXXX  |
| CHKD                                 |  | UNIT: mm/in | DWG NO.: X-X03XXWTXXX |
| APPD                                 |  | SIZE: A4    | WEIGHT SHEET REVISION |
| XKB INDUSTRIAL PRECISION CO.,LIMITED |  |             | 1/1 A0                |

广东星坤科技股份有限公司

| MARK | DESCRIPTION | DATE | REVISED | APPROVED |
|------|-------------|------|---------|----------|
| Δx   |             |      |         |          |
| Δx   |             |      |         |          |
| Δx   |             |      |         |          |

文件工程章

| REVISIONS | DATE | REVISED | APPROVED | UNSPECIFIED TOLERANCES |
|-----------|------|---------|----------|------------------------|
| ANGLAR    |      |         |          | ±5°                    |
| L≤ 4      |      |         |          | ±0.2                   |
| 4<L≤ 16   |      |         |          | ±0.3                   |
| 16<L≤ 63  |      |         |          | ±0.4                   |
| L> 63     |      |         |          | ±0.5                   |



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [D-Sub Standard Connectors](#) category:*

*Click to view products by [XKB](#) manufacturer:*

Other Similar products are found below :

[015-0339-000](#) [015-0341-000](#) [015-0349-000](#) [015-0350-000](#) [015-8544-011](#) [015-8755-001](#) [017041-0005](#) [020419-0104](#) [609-25P](#) [609-9P](#)  
[M24308/2-23Z](#) [CT0-24-10SC](#) [CT0-36-3PC](#) [CT0E20-8PS](#) [CT0F16S-1PS](#) [CT0TA16-11SXCA232](#) [CT1E20-19SS](#) [CT2-10SL-3SC](#) [CT2-14S-2PCA34](#) [CT2-18-11PCAU](#) [CT2-22-19SC](#) [CT2-36-5PC](#) [CT6-10SL-3SC](#) [CT6-10SL-4SC](#) [CT6-14S-2SC](#) [CT6-16-12SC](#) [CT6-18-10PSA206](#)  
[CT6-18-10PSA232](#) [CT6-18-11PXSA206](#) [CT6-18-11PXSA232](#) [CT6-22-10PS](#) [CT6-24-5PC](#) [CT6-9767-18-8-18-4SS](#) [CT6E14S-5SC](#)  
[CT6E14SA7SC](#) [CT6E20-14SS](#) [CT6E22-14PC](#) [CT6E22-14PS](#) [CT6E22-19PS](#) [CT6E22-22PS](#) [CT6E24-10SC](#) [CT6F16S-1SC](#) [CT6FA10SL-4PS](#)  
[CT6LA20-19PC](#) [CT6M20-19SS](#) [CT6NSB4-20-8SS](#) [CT6TC14S-6SCAU](#) [CT6TC14S-7PS](#) [6STD15SCT99S40X](#) [6STF09PCM05B70X](#)