





	3D VIEW							图式			╡╽╴│┊╻╸			
							DSND		DATE		SCALE: N/A	MODEL TY	(PE:	
ΔΧ				!	units: tolerance:		DWN		DATE		VIEW:	PART NO.	:	
					X.X	±0.2mm	СНКД		DATE		UNIT: mm/in	۱		
ΔΧ						±0.1mm ±0.05mm	APPD		DATE		SIZE: A4	DWG NO.:	X03XXFXX	xx
MARK	DESCRIPTION REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED 1		+					, WEIGHT		REVISION
www.xk-dg.cn www.helloxkb.cn							XKB INDUSTRIAL PRECISION CO., LIMITED				,LIMITED	1.0g	1/1	A0
					yse	Autode								









8 [0.211

NO. OF CONTACT	А	В	С
09	30.80	24.99	16.35
15	39.20	33.30	24.75
25	53.05	47.04	38.35
37	69.40	63.50	54.75

铆合方式

$\overline{0} \ \overline{0} \$

Specifications: 规格

Current rating:5A AC/DC

额定电流: 5A AC/DC

() Series N0. QRow No.Pin No.XX-09;15;25;37 Welding Board Angle :F-Fmale (4)T: Tradutional C: Car-pin S Planting Categotry: 1:1U 2:2U 3:3U 4:5U 5:15U 6:30U 7:AuSn B:BLACK W:White BL:Blue Y:Yellow G:Green R:Red

()1:TYPE-1; 2:TYPE-2; 3:TYPE-3; 4:TYPE-4; 5:TYPE-5; 6:TYPE-6

TYPE-1: 铆合 TYPE-6: 直铆锁 TYPE-3: 叉锁 TYPE-2: 铆合锁螺丝

X03 XX F X X X X

Voltage rating:500V AC 额定电压: 500V AC Withstanding voltage:500V AC/MIN 耐受电压: ≥500V AC/分钟 Temperature range:-25 °C-+105 °C 温度范围: -55℃-+105℃ Insulation resistance:1000MΩMIN 绝缘电阻: ≥1000MΩ Contact resistance:30mQMAN 接触电阻:≤30mΩ Materiai And FINISHED: 材料和成本: INSULATOR:PBT+30 % GF UL 94V-0 绝缘体: pbt+30% gf ul 94-0 SHELL:STEEL, NI FINISHED 外壳:钢、聂加工 CONTACT MATERIAL: BRASS SELEVITE GOLD FINISHED 触点材料: 黄铜SELEVITE

Ē

.18[0.116]

2.62 [0.103]

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for HDMI, Displayport & DVI Connectors category:

Click to view products by XKB manufacturer:

Other Similar products are found below :

30-1231 30-528 30-504 30-519 33DVIR-24S1B 47648-2000 2002-400 TC142X 769-103/021-000 1932649-1 CP30200GM3 67881 HBLBH HBLBI HAFBG HAFBH HAGBF HAGBG HAGBJ HBLBJ AABIE AABIF AABIG AABIH AABIJ AABIK AACBE AACBF AACBG ABIBF ABIBG ABIBH AACBH AACBH AACBI AACBJ AACBK AACBL AAIBD AAIBF AAIBI AANBJ AAQBH AAQBI AARBG AARBH AARBI AAXBD ABAAF ABBBF AIDB0