



Recommended PCB
Layout ±0.05

Specifications:

规格:

- Voltage rating:30V AC/DC
- 额定电压: 30V AC/DC
- Current rating:0.3A AC/DC
- 额定电流: 0.3A AC/DC
- Withstanding voltage:100V AC/minute
- 耐受电压: 100V AC/分钟
- Temperature range:-35℃~+85℃
- 温度范围: -35℃~+85℃
- Insulation resistance:50MΩ min
- 绝缘电阻: 50MΩ Min
- Contact resistance:90mΩ Max
- 接触电阻: 90mΩ Max

X0408 F V S - XX X - LP V01

- ① ② ③ ④ ⑤ ⑥ ⑦ ⑧
- 1.Series No
 - 2.Category:F-Female
 - 3.Welding Board Angle:V-Straight 180°
 - 4.Welding Way:S-SMT
 - 5.Row No.Pin No:XX-10~100P
 - 6.Height:A=1.5 ;B=2.0 ;C=2.5 ;D=3.0 ;E=3.5 ;F=4.0mm
 - 7.Material:LP-LCP UL94V-0 Black
 - 8.Plating:V01-Gold Flash

HEIGHT		
H(Socket)	H(Plug)	Mating height
1.45	1.14	A=1.5
1.95		B=2.0
2.40		C=2.5
2.90		D=3.0
3.40		E=3.5
3.90		F=4.0

Poles	Dimensions(mm)		
	A	B	C
10	4.60	1.60	1.00
12	5.00	2.00	
20	6.60	3.60	
24	7.40	4.40	1.20
30	8.60	5.60	1.50
34	9.40	6.40	2.30
40	10.60	7.60	3.20
50	12.60	9.60	
60	14.60	11.60	
70	16.60	13.60	
80	18.60	15.60	
90	20.60	17.60	
100	22.60	19.60	

X0408FVS-XXX-LPV01	LCP	Phosphor Bronze	X0407W
PART NO	Material	Material(Pin)	Suitable XKB Wafer

Δx					ANGLAR	±5°
Δx					L ≤ 4	±0.2
Δx					4 < L ≤ 16	±0.3
MARK	DESCRIPTION	DATE	REVISED	APPROVED	16 < L ≤ 63	±0.4
					L > 63	±0.5
REVISIONS					UNSPECIFIED TOLERANCES	
www.helloxkb.com www.helloxkb.cn www.xk-dg.cn						

DSND		SCALE: N/A	MODEL TYPE: 0.4mm BTB Connector
DWN		VIEW:	PART NO.: X0408FVS-XXX-LPV01
CHKD		UNIT: mm/in	DWG NO.: X-X0408FVS-XXX-LPV01
APPD		SIZE: A4	WEIGHT
XKB INDUSTRIAL PRECISION CO., LIMITED			SHEET
			REVISION
			1/1
			A0

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Board to Board & Mezzanine Connectors](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[589158040000018](#) [MDF7C-18P-2.54DSA\(55\)](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [MIS-048-01-F-D-DP-K](#)
[832-10-034-10-001000](#) [FX4C-80S-1.27DSA](#) [93696-330](#) [224393](#) [FCN-235D050-G/C](#) [210-93-314-41-105000](#) [MDF7-40DP-2.54DSA\(55\)](#)
[55323-1519](#) [069159702701000](#) [101A10019X](#) [105061100000861+](#) [75140-7012](#) [87471-650](#) [1744382-4](#) [063209](#) [10124054-515LF](#) [68685-603](#)
[8-1616154-3](#) [541371078](#) [IL-WX-10PB-HF-B-E1000E](#) [FX23-40P-0.5SV15B](#) [FCN-214J100-G/0](#) [354184](#) [P50-028-DDS-TG](#) [53309-2471](#)
[54546-2071](#) [1586617-1](#) [504248-1210](#) [504248-2010](#) [1-1437355-2](#) [9159005551906](#) [NDS100-004-BF](#) [93696-730LF](#) [91922-31141LF](#) [505274-](#)
[3440](#) [501493-2410](#) [504208-3410](#) [505006-0811](#) [505274-2040](#) [202436-1600](#) [202477-0414](#) [71660-7580](#) [73420-5192](#) [360-10-107-00-001000](#)