



Specifications:

规格:

1.Voltage rating:250VAC/DC  
额定电压: 250V AC/DC

2.Current rating:3A AC/DC  
额定电流: 3A AC/DC

3.Withstanding voltage:500V AC/minute  
耐受电压: 500V AC/分钟

4.Temperature range: -55°C~+105°C  
温度范围: -55°C~+105°C

5.Insulation resistance:1000MΩ MIN  
绝缘电阻: 1000MΩ MIN

6.Contact resistance:30mΩ Max  
接触电阻: 30mΩ Max

Material:

材料:

7.Rubber core:PBT UL94V-0  
胶芯: PBT UL94V-0

8.The iron shell:SPCC-SD Nivkel Plating/Tin Plating/Gold Plating  
铁壳: SPCC-SD, 镀镍/镀锡/镀金

9.Terminal:Copper alloy  
端子: 铜合金

10. Terminal: Copper alloy  
端子: 铜合金

11. Terminal: Copper alloy  
端子: 铜合金

12. Terminal: Copper alloy  
端子: 铜合金

13. Terminal: Copper alloy  
端子: 铜合金

14. Terminal: Copper alloy  
端子: 铜合金

15. Terminal: Copper alloy  
端子: 铜合金

X04 XX F X X X X

① ② ③ ④ ⑤ ⑥ ⑦

① Series NO.

② Row No.Pin No:XX-09;15;25;37

③ Welding Board Angle: F-Female

④ T: Tradutional C: Car-pin

⑤ Planting Catogtry: 1:1U 2:2U 3:3U 4:5U 5:15U 6:30U 7:AuSn

⑥ Color:B-BLACK W-White BL-Blue

⑦ 1:TYPE-1; 2:TYPE-2; 3:TYPE-3; 4:TYPE-4

NUMBER OF POSITIONS	DIMENSION			
	A±0.25	B±0.13	C±0.38	D±0.25
15	16.35	24.99	30.80	19.28
26	24.75	33.32	39.20	27.51
44	38.35	47.04	53.05	41.28
62	54.75	63.50	69.40	57.71

耦合方式	TYPE-1: 耦合	TYPE-2: 前侧实心螺母	TYPE-3: 后侧空心螺母	TYPE-4: 后侧空心螺母锁螺丝
图示				

DSND		SCALE: N/A	MODEL TYPE: D-SUB
DWN		VIEW:	PART NO.: X04XXFXXXX
CHKD		UNIT: mm/in	DWG NO.: X-X04XXFXXXX
APPD		SIZE: A4	WEIGHT SHEET REVISION
KKB INDUSTRIAL PRECISION CO., LIMITED			1/1 A0

**XKIB**

MARK	DESCRIPTION	DATE	REVISED	APPROVED	ANGLAR	±5°
ΔX					L ≤ 4	±0.2
ΔX					4 < L ≤ 16	±0.3
ΔX					16 < L ≤ 63	±0.4
					L > 63	±0.5
REVISIONS					UNSPECIFIED TOLERANCES	
www.helloxkb.com www.helloxkb.cn www.xk-dg.cn						

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [D-Sub Standard Connectors](#) category:*

*Click to view products by [XKB](#) manufacturer:*

Other Similar products are found below :

[015-0339-000](#) [015-0341-000](#) [015-0349-000](#) [015-0350-000](#) [015-8544-011](#) [015-8755-001](#) [017041-0005](#) [020419-0104](#) [609-25P](#) [609-9P](#)  
[M24308/2-23Z](#) [CT0-24-10SC](#) [CT0-36-3PC](#) [CT0E20-8PS](#) [CT0F16S-1PS](#) [CT0TA16-11SXCA232](#) [CT1E20-19SS](#) [CT2-10SL-3SC](#) [CT2-14S-2PCA34](#) [CT2-18-11PCAU](#) [CT2-22-19SC](#) [CT2-36-5PC](#) [CT6-10SL-3SC](#) [CT6-10SL-4SC](#) [CT6-14S-2SC](#) [CT6-16-12SC](#) [CT6-18-10PSA206](#)  
[CT6-18-10PSA232](#) [CT6-18-11PXSA206](#) [CT6-18-11PXSA232](#) [CT6-22-10PS](#) [CT6-24-5PC](#) [CT6-9767-18-8-18-4SS](#) [CT6E14S-5SC](#)  
[CT6E14SA7SC](#) [CT6E20-14SS](#) [CT6E22-14PC](#) [CT6E22-14PS](#) [CT6E22-19PS](#) [CT6E22-22PS](#) [CT6E24-10SC](#) [CT6F16S-1SC](#) [CT6FA10SL-4PS](#)  
[CT6LA20-19PC](#) [CT6M20-19SS](#) [CT6NSB4-20-8SS](#) [CT6TC14S-6SCAU](#) [CT6TC14S-7PS](#) [6STD15SCT99S40X](#) [6STF09PCM05B70X](#)