

Recommended PCB LAYOUT

Specifications:

规格:
Voltage rating:100V AC/DC
额定电压: 100V AC/DC
Current rating:0.3A AC/DC
额定电流: 0.3A AC/DC
Withstanding voltage:150V AC/minute
耐受电压: 150V AC/分钟
Temperature range:-40°C~+125°C
温度范围: -40°C~+125°C
Insulation resistance:100MΩ min
绝缘电阻: 100MΩ Min
Contact resistance:50mΩ Max
接触电阻: 50mΩ Max

X0502 F V S - XX X X S - LP SN
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

1. Series No
2. Category:F-Female
3. Welding Board Angle:V-Stright 180°
4. Welding Way:S-SMT
5. Row No. Pin No:XX-10~80P
6. Height:A:2.2mm; B:2.3mm; C:2.9mm;
7. Type: Blank-There are no side two ground tags
 1-There are with side two ground tags
8. Special No:S-With positioning column
9. Material:LP-LCP UL94V-0
10. Plating:SN-Tin Plated or V01-Gold Flash

Mating Height	PLUG	SOCKET
3.0	2.1	2.2
3.4	2.2	2.3
4.0	2.2	2.9
5.0	2.7	4.3

Poles	Dimensions(mm)				Poles	Dimensions(mm)			
	A	B	C	D		A	B	C	D
10	4.70	2.00	3.20	4.10	32	10.20	7.50	8.70	9.60
12	5.20	2.50	3.70	4.60	36	11.20	8.50	9.70	10.60
14	5.70	3.00	4.20	5.10	40	12.20	9.50	10.70	11.60
20	7.20	4.50	5.70	6.60	50	14.70	12.00	13.20	14.60
22	7.70	5.00	6.20	7.10	60	17.20	14.50	15.70	16.60
24	8.20	5.50	6.70	7.60	80	22.20	19.50	20.70	21.60
30	9.70	7.00	8.20	9.10	/				

X0502FVS-XXXS-LPSN	LCP	Copper Alloy	X0502W
PART NO	Material	Material(Pin)	Suitable XKB Wafer

DSND	SCALE: N/A	MODEL TYPE:
DWN	VIEW:	0.5mm BTB Connector
CHKD	UNIT: mm/in	PART NO.: X0502FVS-XXXS-LPSN
APPD	SIZE: A4	DWG NO.: X-X0502FVS-XXXS-LPSN
		WEIGHT SHEET REVISION
		1/1 A0





XKB INDUSTRIAL PRECISION CO.,LIMITED

ANGLAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5

UNSPECIFIED TOLERANCES

MARK	DESCRIPTION	DATE	REVISED	APPROVED
ΔX				
ΔX				
ΔX				

REVISIONS



Specifications:

规格:

Voltage rating:100V AC/DC

额定电压: 100V AC/DC

Current rating:0.3A AC/DC

额定电流: 0.3A AC/DC

Withstanding voltage:150V AC/minute

耐受电压: 150V AC/分钟

Temperature range:-40℃~+125℃



温度范围: -40℃~+125℃

Insulation resistance:100MΩ min

绝缘电阻: 100MΩ Min

Contact resistance:50mΩ Max


接触电阻: 50mΩ Max



X0502 F V S - XX D X S - LP SN

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

1. Series No
2. Category: F-Female
3. Welding Board Angle: V-Stright 180°
4. Welding Way: S-SMT
5. Row No. Pin No: XX-10~80P
6. Height: D:4.3mm
7. Type: Blank-There are no side two ground tags
 - 1-There are with side two ground tags
8. Special No: S-With positioning column
9. Material: LP-LCP UL94V-0
10. Plating: SN-Tin Plated or V01-Gold Flash



Recommended PCB LAYOUT

Mating Height	PLUG	SOCKET
3.0	2.1	2.2
3.4	2.2	2.3
4.0	2.2	2.9
5.0	2.7	4.3

Poles	Dimensions(mm)						Poles	Dimensions(mm)					
	A	B	C	D	E	F		A	B	C	D	E	F
10	4.70	2.00	3.20	3.30	5.45	4.10	50	14.70	12.00	13.20	13.30	15.45	14.10
20	7.20	4.50	5.70	5.80	7.95	6.60	60	17.20	14.50	15.70	15.80	17.95	16.60
30	9.70	7.00	8.20	8.30	10.45	9.10	68	19.20	16.50	17.70	17.80	19.95	18.60
36	11.20	8.50	9.70	9.80	11.95	10.60	70	19.70	17.00	18.20	18.30	20.45	19.10
40	12.20	9.50	10.80	10.80	12.95	11.60	80	22.20	19.50	20.70	20.80	22.95	21.60

X0502FVS-XXDS-LPSN	LCP	Copper Alloy	X0502W
PART NO	Material	Material(Pin)	Suitable XKB Wafer

DSND		SCALE: N/A	MODEL TYPE: 0.5mm BTB Connector
DWN		VIEW:	PART NO.:
CHKD		UNIT: mm/in	X0502FVS-XXDS-LPSN
APPD		SIZE: A4	DWG NO.:
			X-X0502FVS-XXDS-LPSN
			WEIGHT
			SHEET
			REVISION
			1/1
			A0



XKB INDUSTRIAL PRECISION CO., LIMITED

ANGLAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5
UNSPECIFIED TOLERANCES	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Board to Board & Mezzanine Connectors](#) category:

Click to view products by [XKB](#) manufacturer:

Other Similar products are found below :

[589158040000018](#) [MDF7C-18P-2.54DSA\(55\)](#) [FCN-268F036-G/BD](#) [FCN-268M012-G/0D](#) [FCN-268M024-G/1D](#) [MIS-048-01-F-D-DP-K](#)
[832-10-034-10-001000](#) [FX4C-80S-1.27DSA](#) [93696-330](#) [224393](#) [FCN-235D050-G/C](#) [210-93-314-41-105000](#) [MDF7-40DP-2.54DSA\(55\)](#)
[55323-1519](#) [069159702701000](#) [101A10019X](#) [105061100000861+](#) [75140-7012](#) [87471-650](#) [1744382-4](#) [063209](#) [10124054-515LF](#) [68685-603](#)
[8-1616154-3](#) [541371078](#) [IL-WX-10PB-HF-B-E1000E](#) [FX23-40P-0.5SV15B](#) [FCN-214J100-G/0](#) [354184](#) [P50-028-DDS-TG](#) [53309-2471](#)
[54546-2071](#) [1586617-1](#) [504248-1210](#) [504248-2010](#) [1-1437355-2](#) [9159005551906](#) [NDS100-004-BF](#) [93696-730LF](#) [91922-31141LF](#) [505274-](#)
[3440](#) [501493-2410](#) [504208-3410](#) [505006-0811](#) [505274-2040](#) [202436-1600](#) [202477-0414](#) [71660-7580](#) [73420-5192](#) [360-10-107-00-001000](#)